

# SAFETY DATA SHEET



8-145 HS Surfacers Grey

## Section 1. Identification

**Product name** : 8-145 HS Surfacers Grey

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

### Identified uses

Use in coatings - Priming materials and coatings

### Supplier

**Manufacturer** : Valspar b.v.  
Zuiveringweg 89  
8243 PE Lelystad  
The Netherlands  
tel: +31 (0)320 292200  
fax: +31 (0)320 292201

**Emergency telephone number** : Call: +31 (0)320 292200 (during daytime)

**Supplier's details** : DBNZ Coatings Limited  
6 Killarney Lane  
Hamilton 3204  
NEW ZEALAND  
T: +64 7847 0944  
E: info@dbnz.co.nz

**Emergency telephone number (with hours of operation)** : New Zealand Poisons Information Centre: 0800 764766 (24 hrs)

CALL: +(64)-98010034 (Hours of operation - 24 hours)

**e-mail address of person responsible for this SDS** : msds@de-beer.com

## Section 2. Hazards identification

**HSNO Classification** : FLAMMABLE LIQUIDS - Category 3  
EYE IRRITATION - Category 2  
CARCINOGENICITY - Category 2  
REPRODUCTIVE TOXICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2  
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2  
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

### GHS label elements

**Signal word** : Warning

**Hazard statements** : Flammable liquid and vapour.  
Causes serious eye irritation.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs.  
May cause damage to organs through prolonged or repeated exposure.  
Toxic to aquatic life with long lasting effects.

### Precautionary statements

## Section 2. Hazards identification

- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Do not breathe vapour or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
- Response** : Collect spillage. IF exposed or concerned: Call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Store locked up.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Symbol** :



**Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	% (w/w)	CAS number
n-butyl acetate	10.444	123-86-4
trizinc bis(orthophosphate)	7.0928	7779-90-0
xylene	6.8428	1330-20-7
Solvent naphtha (petroleum), light arom.	6.0801	64742-95-6
ethylbenzene	1.6604	100-41-4
zinc oxide	0.28371	1314-13-2
aluminium sulphate	0.16888	10043-01-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## Section 4. First aid measures

- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Inhalation** : May cause damage to organs following a single exposure if inhaled.
- Ingestion** : May cause damage to organs following a single exposure if swallowed.
- Skin contact** : May cause damage to organs following a single exposure in contact with skin.
- Eye contact** : Causes serious eye irritation.

#### Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : Not available.
- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Specific hazards arising from the chemical** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides  
phosphorus oxides  
metal oxide/oxides

## Section 5. Firefighting measures

- Hazchem code** : 3Y
- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

- Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
n-butyl acetate	<b>NZ HSWA 2015 (New Zealand, 11/2018).</b> WES-TWA: 150 ppm 8 hours. WES-TWA: 713 mg/m <sup>3</sup> 8 hours. WES-STEL: 950 mg/m <sup>3</sup> 15 minutes. WES-STEL: 200 ppm 15 minutes.
xylene	<b>NZ HSWA 2015 (New Zealand, 11/2018).</b> <b>Notes: See Notice of Intended Changes.</b> WES-TWA: 217 mg/m <sup>3</sup> , 0 times per shift, 8 hours. WES-TWA: 50 ppm, 0 times per shift, 8 hours.
ethylbenzene	<b>NZ HSWA 2015 (New Zealand, 11/2018).</b> WES-STEL: 543 mg/m <sup>3</sup> 15 minutes. WES-STEL: 125 ppm 15 minutes. WES-TWA: 434 mg/m <sup>3</sup> 8 hours. WES-TWA: 100 ppm 8 hours.
zinc oxide	<b>NZ HSWA 2015 (New Zealand, 11/2018).</b> WES-STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Fume WES-TWA: 3 mg/m <sup>3</sup> , (Respirable fraction) 8 hours. Form: Respirable fume WES-TWA: 10 mg/m <sup>3</sup> 8 hours. Form: The value for respirable dust.
aluminium sulphate	<b>NZ HSWA 2015 (New Zealand, 11/2018).</b> WES-TWA: 5 mg/m <sup>3</sup> , (as Al) 8 hours.

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: EN 405:2001 + A1:2009 organic vapour (Type A) and particulate filter FFA2P3 R D

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 polyvinyl alcohol (PVA) >= 0.7 mm  
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves;

## Section 8. Exposure controls/personal protection

EN 374: Nitrile rubber - NBR ( $\geq 0.35$  mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.

- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: chemical splash goggles and/or face shield.
- Skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Colour** : Grey.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Not available.
- Boiling point** :  $>100^{\circ}\text{C}$  ( $>212^{\circ}\text{F}$ )
- Flash point** : Closed cup:  $28^{\circ}\text{C}$  ( $82.4^{\circ}\text{F}$ )
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 0.8%  
Upper: 7%
- Vapour pressure** : Not available.
- Vapour density** : 4 [Air = 1]
- Relative density** : 1.62
- Solubility** : Insoluble in the following materials: cold water and hot water.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Flow time (ISO 2431)** : Not available.

### Aerosol product

- Type of aerosol** : Not applicable.
- Heat of combustion** : Not available.
- Ignition distance** : Not applicable.
- Enclosed space ignition - Time equivalent** : Not applicable.
- Enclosed space ignition - Deflagration density** : Not applicable.
- Flame height** : Not applicable.
- Flame duration** : Not applicable.



## Section 10. Stability and reactivity

<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.
<b>Incompatible materials</b>	: Reactive or incompatible with the following materials: oxidising materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	: May cause damage to organs following a single exposure if inhaled.
<b>Ingestion</b>	: May cause damage to organs following a single exposure if swallowed.
<b>Skin contact</b>	: May cause damage to organs following a single exposure in contact with skin.
<b>Eye contact</b>	: Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation</b>	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
<b>Ingestion</b>	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
<b>Skin contact</b>	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
<b>Eye contact</b>	: Adverse symptoms may include the following: pain or irritation watering redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>14112 mg/kg	-
	LD50 Oral	Rat	10760 mg/kg	-
trizinc bis(orthophosphate)	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
xylene	LC50 Inhalation Gas.	Rat	6350 ppm	4 hours
	LD50 Dermal	Rabbit	12126 mg/kg	-
	LD50 Oral	Rat	3523 to 4000 mg/kg	-
Solvent naphtha (petroleum), light arom.	LC50 Inhalation Vapour	Rat	6193 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>3160 mg/kg	-
	LD50 Oral	Rat	3592 mg/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	6350 ppm	4 hours
	LD50 Dermal	Rabbit	12126 mg/kg	-
	LD50 Oral	Rat	3523 to 4000 mg/kg	-
zinc oxide	LC50 Inhalation Dusts and mists	Rat	>5.7 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

## Section 11. Toxicological information

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
zinc oxide	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
aluminium sulphate	Eyes - Severe irritant	Rabbit	-	24 hours 10 milligrams	-

### Sensitisation

Not available.

### Potential chronic health effects

<b>General</b>	: May cause damage to organs through prolonged or repeated exposure.
<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Ingestion</b>	: No known significant effects or critical hazards.
<b>Skin contact</b>	: No known significant effects or critical hazards.
<b>Eye contact</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: Suspected of damaging the unborn child.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: Suspected of damaging fertility.

### Chronic toxicity

Not available.

### Carcinogenicity

Not available.

### Mutagenicity

Not available.

### Teratogenicity

Not available.

### Reproductive toxicity

Not available.

### Specific target organ toxicity

Name	Category	Route of exposure	Target organs
xylene	Category 2	oral, inhalation	-
ethylbenzene	Category 2	inhalation	-

### Aspiration hazard



## Section 11. Toxicological information

### Name

Solvent naphtha (petroleum), light arom.  
ethylbenzene

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	7307 mg/kg
Dermal	16075.4 mg/kg
Inhalation (gases)	92798.89 ppm
Inhalation (vapours)	662.48 mg/l
Inhalation (dusts and mists)	14.36 mg/l

## Section 12. Ecological information

**Ecotoxicity** : This material is toxic to aquatic life with long lasting effects.

### Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
n-butyl acetate	Acute EC50 397 mg/l	Algae - Selenastrum capricornutum	72 hours
	Acute EC50 44 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 32 mg/l	Crustaceans - Artemia salina	48 hours
	Acute LC50 18 mg/l	Fish - Pimephales promelas	96 hours
	Acute NOEC 200 mg/l	Algae	72 hours
trizinc bis(orthophosphate)	Acute EC50 63.1 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 6.3 mg/l	Fish - Oncorhynchus mykiss	96 hours
xylene	Acute EC50 1 to 10 mg/l	Algae	72 hours
	Acute EC50 1 to 10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 1 to 10 mg/l	Fish	96 hours
Solvent naphtha (petroleum), light arom.	Acute EC50 2.9 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3.2 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 9.2 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute NOEC >1 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
ethylbenzene	Acute LC50 >10 mg/l	Fish - Pimephales promelas	96 hours
zinc oxide	Acute EC50 0.17 mg/l	Algae - Selenastrum capricornutum	72 hours
	Acute LC50 320 ppm	Fish - Lepomis macrochirus	96 hours
	Chronic NOEC 0.017 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
aluminium sulphate	Acute EC50 6570 µg/l Fresh water	Crustaceans - Asellus aquaticus - Adult	48 hours
	Acute IC50 167 µg/l Fresh water	Algae - Chlorella sp. - Exponential growth phase	72 hours
	Acute IC50 3200 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 4.4 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 4 µg/l Fresh water	Fish - Salvelinus fontinalis - Eyed stage, eyed embryo	30 days

### Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	OECD 301D Ready Biodegradability - Closed Bottle Test	>80 % - 5 days	-	-
Solvent naphtha (petroleum), light arom.	-	78 % - Readily - 28 days	-	Fresh water

## Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	-	-	Readily
Solvent naphtha (petroleum), light arom.	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-butyl acetate	2.3	-	low
trizinc bis(orthophosphate)	-	60960	high
xylene	3.12	8.1 to 25.9	low
Solvent naphtha (petroleum), light arom.	-	10 to 2500	high
ethylbenzene	3.6	-	low
zinc oxide	-	28960	high
aluminium sulphate	-	362	low

### Mobility in soil







**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.




## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>New Zealand Class</b>	UN1263	PAINT	3	III	 
<b>ADG Class</b>	UN1263	PAINT	3	III	
<b>UN Class</b>	UN1263	PAINT	3	III	
<b>ADR/RID Class</b>	UN1263	PAINT	3	III	 

## Section 14. Transport information

<b>IATA Class</b>	UN1263	Paint	3	III	
<b>IMDG Class</b>	UN1263	PAINT	3	III	 

### Additional information

- New Zealand Class** : The marine pollutant mark is not required when transported by road or rail.  
**Hazchem code** 3Y  
**Special provisions** 163, 223
- ADG Class** : **Hazchem code** •3Y  
**Special provisions** 163, 223, 367
- UN Class** : **Special provisions** 163, 223, 367
- ADR/RID Class** : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Hazard identification number** 30  
**Limited quantity** 5 L  
**Special provisions** 163, 640E, 650, 367  
**Tunnel code** (D/E)
- IATA Class** : The environmentally hazardous substance mark may appear if required by other transportation regulations.  
**Quantity limitation** Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 10 L. Packaging instructions: Y344.  
**Special provisions** A3, A72, A192
- IMDG Class** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  
**Emergency schedules** F-E, \_S-E\_  
**Special provisions** 163, 223, 367, 955

PG\* : Packing group

**Transport in bulk according to IMO instruments** : Not available.

## Section 15. Regulatory information

- HSNO Approval Number** : HSR002669
- HSNO Group Standard** : Surface Coatings and Colourants
- HSNO Classification** : FLAMMABLE LIQUIDS - Category 3  
 EYE IRRITATION - Category 2  
 CARCINOGENICITY - Category 2  
 REPRODUCTIVE TOXICITY - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2  
 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

## Section 15. Regulatory information

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

<b>Australia</b>	: All components are listed or exempted.
<b>Canada</b>	: At least one component is not listed in DSL but all such components are listed in NDSL.
<b>China</b>	: All components are listed or exempted.
<b>Europe</b>	: All components are listed or exempted.
<b>Japan</b>	: <b>Japan inventory (CSCL)</b> : Not determined. <b>Japan inventory (ISHL)</b> : Not determined.
<b>Malaysia</b>	: Not determined
<b>New Zealand</b>	: All components are listed or exempted.
<b>Philippines</b>	: Not determined.
<b>Republic of Korea</b>	: All components are listed or exempted.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Thailand</b>	: Not determined.
<b>Turkey</b>	: Not determined.
<b>United States</b>	: Not determined.
<b>Viet Nam</b>	: Not determined.

## Section 16. Other information

### History

<b>Date of printing</b>	: 6/4/2022
<b>Date of issue/Date of revision</b>	: 6/4/2022
<b>Date of previous issue</b>	: 4/12/2022
<b>Version</b>	: 1

<b>Key to abbreviations</b>	: ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
-----------------------------	---

<b>References</b>	: Not available.
-------------------	------------------

Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.