



1-141 Uni Thinner Fast

APPLICATION DATA




: See application data on our products.



Application viscosity
DINCUP 4mm/20°C

: Airspray (sec) : -
: Pressure tank (sec) : -
: Airless (sec) : -
-



Gravity feed
Suction feed
Pressure tank
Airless
HVLP / LVLP
HE


Nozzle diameter (mm)

Spraying pressure (bar)

-
-
-
-
-
See Info Manufacturer
See Info Manufacturer



Spray coats / Layer thickness
(µm) : - / -



Flash-off (min) : -



Drying time (min) **20°C** : -
 60°C Obj. : -



Potlife (min) **20°C** : -

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.

1-141 Uni Thinner Fast



PRODUCT INFO

- Area of application** : Thinners for amongst others Series 400 and Series 500. Do not use in combination with synthetic products, Series 900, Series 3000 HS420.
- Chemical base** : Organic solvents thinners.
- General qualities** : 1-141 Uni Thinner Fast for application at 12°- 18°C, and spotrepair.
- Auxiliary materials** : All products except Synthetic products

Physical properties	Specific gravity (kg/l)	: 0.876
	Flash point	: Closed cup: 25°C (77°F)
	Vol.% solids	: 0
	Economy	: -
	Gloss	:
	Colour	: Clear.

- Substrates** : See application data on our products:
- Undercoats** : See application data on our products
- Finishing materials** : See application data on our products
- Cleaning the equipment** : -
- Storage life (years)** : min. 2
(Under normal storage conditions and unopened tins).

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.