

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Plastifill 750ml
UFI : CR27-X8FT-HQCQ-RDPP
Product code : GAP 70

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Bodyfiller/stopper

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Importer

Paint Smart Group NZ
6 Killarney Lane
Hamilton
T +64 7 847 0933 - F +64 7 847 0932
www.paintsmart.co.nz

Supplier

Chemical Europe
Baarbeek 2
2070 Zwijndrecht, Belgium
T +32 3 234 87 80
www.finixa.com

1.4. Emergency telephone number

Emergency number : Poisons Information Centre New Zealand
0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity — Repeated exposure, Category 1	H372
Skin sensitisation, category 1A	H317

Full text of H statements : see section 16
HSR002662 - HSNO Group Standard Surface Coatings and Colourants (Flammable)

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	GHS02	GHS07	GHS08
Signal word (CLP)	: Danger		
Contains	: styrene; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2- ((2-(2-hydroxyethoxy)ethyl)(4-methylphenyl)amino)-		
Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H361d - Suspected of damaging the unborn child. H372 - Causes damage to organs through prolonged or repeated exposure.		
Precautionary statements (CLP)	: P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe vapours. P280 - Wear protective gloves, eye protection. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.		

Scandinavian countries regulation

Denmark

MAL code : 4-6

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
styrene	(CAS-No.) 100-42-5 (EC-No.) 202-851-5 (EC Index-No.) 601-026-00-0	15 – 20	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2- ((2-(2-hydroxyethoxy)ethyl)(4-methylphenyl)amino)-	(EC-No.) 911-490-9	0.25 – 0.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	0.01 – 0.1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 1, H372

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Then ventilate the premises. Get immediate medical advice/attention. Move the affected person away from the contaminated area and into the fresh air.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Rinse skin with water/shower.

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after eye contact	: Rinse opened eye for several minutes under running water. Then consult doctor. Protect undamaged eye.
First-aid measures after ingestion	: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Refer to chapter 8. For further information refer to section 13.
------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry extinguishing powder. carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Water.

5.2. Special hazards arising from the substance or mixture

Explosion hazard	: In case of fire and/or explosion do not breathe fumes.
Reactivity in case of fire	: Fire will produce dense black smoke. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Precautionary measures fire	: Move containers from fire area if it can be done without personal risk.
Protection during firefighting	: Approved respirator.
Other information	: Prevent fire fighting water from entering the environment. Dyke fire control water for later disposal.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing. Warn road users and passers by to keep away from danger area. Eliminate every possible source of ignition.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment. See Heading 8.
----------------------	--

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter drains or water courses. Dam up the solid spill. Notify authorities if product enters sewers or public waters. Contain or absorb spilled liquid with non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Minimise generation of dust. On land, sweep or shovel into suitable containers.
-------------------------	---

6.4. Reference to other sections

SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with skin and eyes. Do not breathe vapours. Handle and open container with care. Refer to chapter 8.
-------------------------------	--

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.
Storage conditions : Keep container tightly closed.
Heat and ignition sources : Use and store away from all naked flames, heat sources or working electrical appliances.
Do not smoke. All heat sources, including direct sunlight.
Storage area : Store in a well-ventilated place. Keep away from food and drink.

7.3. Specific end use(s)

1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Control Parameters	
100-42-5 Styrene	
EU- TWA(8h) STEL()	85 mg/M3, 20 ppm 170 mg/m3, 40 ppm Notes: Pelle
ACGIH – TWA (8H) STEL	10 ppm 20 ppm Notes: OTO, A3,BE1 CNS and hearing impair, URT irr, peripheral neuropathy, visual disorders
Italy – TWA(8h) STEL	20 ppm 200 ppm
108-31-6 maleic anhydride	
ACGIH – TWA(8h)	0.01 mg/m3 - Notes: (IFV), DSEN, RSEN, A4 - Resp sens
DNEL Exposure Limit Values	
100-42-5 styrene	
Worker Professional Consumer Exposure	406 mg/kg 343 mg/kg Human Dermal - Frequency: Long Term, systemic effects Consumer: 2.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects – Worker Professional: 85 mg/m³ - Consumer: 10.2 mg/m³ - Exposure: Human Inhalation – Frequency: Long Term, systemic effects Worker Professional: 289 mg/m³ - Consumer: 174.25 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects Worker Professional: 306 mg/m³ - Consumer: 182.75 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	
	Worker Professional: 9.8 mg/m³ - Consumer: 2.9 mg/m³ - Exposure: Human Inhalation – Frequency: Long Term, systemic effects Worker Professional: 1.4 mg/kg - Consumer: 0.83 mg/kg - Exposure: Human Dermal – Frequency: Long Term, systemic effects Consumer: 0.83 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects
PNEC Exposure Limit Values	
100-425 Styrene	
Target	Fresh Water - Value: 0.028 mg/l Marine water - Value: 0.028 mg/l Freshwater sediments - Value: 0.614 mg/kg Marine water sediments - Value: 0.0614 mg/kg Soil (agricultural) - Value: 0.2 mg/kg Value: 0.04 mg/l Purification plant - Value: 5 mg/l
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-	
Target	Fresh Water - Value: 0.048 mg/l Marine water - Value: 0.0048 mg/l Marine water (intermittent emissions) - Value: 0.48 mg/l Freshwater sediments - Value: 1.2 mg/kg Marine water sediments - Value: 0.12 mg/kg Soil - Value: 0.21 mg/kg

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Control Parameters

100-42-5 Styrene

Biological Exposure Index

100-42-5 styrene

Value: 400 mg/g creatinine - medium: Urine - Biological Indicator: Mandelic acid in urine and fenilgliossilico - Sampling Period: End of turn Value: 40 mg/l creatinine - medium: Urine - Biological Indicator: Styrene in urine - Sampling Period: End of turn

8.2. Exposure controls

Materials for protective clothing:

Take off immediately all contaminated clothing.

Condition	Material	Standard
	Tyvek®	EN 14605

Hand protection:

protective gloves. VITON gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
		3 (> 60 minutes)	≥ 0.7		EN ISO 374

Eye protection:

Safety glasses

Skin and body protection:

Type	Standard
	EN 14605

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
	Type A - High-boiling (>65 °C) organic compounds		

Personal protective equipment symbol(s):



Other information:

Keep away from food and drink. Take off immediately all contaminated clothing. Wash hands before breaks and after work. Avoid contact with skin and eyes.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: No data available
Appearance	: Paste.
Colour	: dark grey.
Odour	: characteristic.
Odour threshold	: 0.15 – 0.25 ppm
pH	: No data available

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -31 °C
Boiling point	: 145 °C
Flash point	: 32 °C
Auto-ignition temperature	: 490 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 6.7 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.33 g/cm ³
Solubility	: Insoluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40°C)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

May react violently with combustible materials. Reacts vigorously with strong oxidizers and acids.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: LD50 oral rat
Acute toxicity (dermal)	: LD50 dermal rat
Acute toxicity (inhalation)	: LC50 Inhalation - Rat (Dust/Mist)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction. (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity	: May damage the unborn child.
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure.
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

Plastifill 750ml

Viscosity, kinematic	> 20.5 mm²/s (40°C)
----------------------	---------------------

Toxicological information of the main substances found in the product

100-42-5 Styrene

acute toxicity:	Test: LD50	Route: Oral - Species: Rat = 5000 mg/kg
	Test: LC50	Inhalation - Species: Rat = 11.8 mg/l - Duration: 4h
STOT-repeated exposure:	Test: LD50	Route: Skin - Species: Rat > 2000 mg/kg - Notes: OECD 402
	Test: LOAEL(C)	Route: Oral - Species: Rat = 2000 mg/kg - Notes: bw/day
	Test: NOAEL(C)	Route: Oral - Species: Rat = 1000 mg/kg - Notes: bw/day
	Test: LOAEL(C)	Route: Inhalation - Species: Rat = 0.21 mg/l

Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]

a) acute toxicity:	Test LD 50 - Route: Oral	Rat = 619 mg/kg
	Test: LD 50 – Route Skin	Rabbit > 2000 mg/kg

100-42-5 Styrene

Acute inhalation toxicity at 1000 ppm affects the central nervous system with headaches, dizziness and coordination difficulties; irritation of the mucous membranes of the eyes and respiratory tract occurs at 500 ppm. Chronic exposure gives system depression central and peripheral nervous system with memory loss, headaches and somnolence starting from 20 ppm; digestive disorders with nausea e loss of appetite; respiratory tract irritation with chronic bronchitis; dermatosis. Repeated exposure, to low doses of the substance by inhalation, it causes irreversible changes in hearing function and can cause changes in color vision. Repeated skin exposures cause irritation. The substance degreases the skin, which can cause dryness and cracking

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Additional information	: No data available.

100-42-5 Styrene

Aquatic acute toxicity	Endpoint: LC50 – Species: Fish	4.02 mg/l - Duration h: 96
	Endpoint: EC 50 – Species: Algae	4.9 mg/l - Duration h: 72
	Endpoint: EC 50 - Species: Daphnia	4.7 mg/kg - Duration h: 48
Aquatic chronic toxicity	Endpoint: EC10 - Species: Algae	0.28 mg/l - Duration h: 96
	Endpoint: NOEC – Species: Daphnia	1.01 mg/l - Duration h: 504

Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol, 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]

Aquatic acute toxicity	Endpoint: LC50	>100 mg/l
	Endpoint EC 50	Daphnia : 48 mg/l
	Endpoint: EC50	Algae > 100 mg/l

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

Plastifill 750ml

Ecology - soil

Do not flush into surface water or sewer system. Danger of drinking-water pollution (ground water). Hazardous to water (WGK 2). May cause long-term adverse effects in the aquatic environment.

12.5. Results of PBT and vPvB assessment

Plastifill 750ml

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods




Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Do not dispose of the packaging without first carrying out the necessary cleaning.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
UN 3269	UN 3269	UN 3269	Not applicable
14.2. UN proper shipping name			
POLYESTER RESIN KIT	POLYESTER RESIN KIT	Polyester resin kit	Not applicable
Transport document description			
UN 3269 POLYESTER RESIN KIT (), 3, III, (E)	UN 3269 POLYESTER RESIN KIT, 3, III	UN 3269 Polyester resin kit, 3, III	Not applicable
14.3. Transport hazard class(es)			
3	3	3	Not applicable
			Not applicable
14.4. Packing group			
III	III	III	Not applicable

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.5. Environmental hazards

Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
---------------------------------------	--	---------------------------------------	---------------------------------------

No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E0
Transport category (ADR)	: 3
Tunnel restriction code (ADR)	: E
EAC code	: •2YE

Transport by sea

Limited quantities (IMDG)	: 5 L
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Properties and observations (IMDG)	: Polyester resin kits consist of two components: a base material (flammable liquid, packaging group II) and an activator (organic peroxide), each separately packed in an inner packaging.

Air transport

No data available

Inland waterway transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on
3.	styrene
3(a)	styrene
3(b)	styrene
40.	styrene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
Storage class (LGK)	: LGK 3 - Flammable liquids

Netherlands

Waterbezwaarlijkheid	: 10 - Weinig schadelijk voor in het water levende organismen; kan in het aquatisch milieu op lange termijn schadelijke effecten veroorzaken.
----------------------	---

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Saneringsinspanningen	: A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: styrene is listed
Denmark	
Class for fire hazard	: Class II-1
Store unit	: 5 liter
Classification remarks	: R10 <H226;H315;H317;H319;H361d;H372>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.

Plastifill 750ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.