



Safety Data Sheet

© 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-2728-5	Version number:	1.00
Issue Date:	10/03/2021	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Specialty Adhesive Remover, PN 38987

Product Identification Numbers

60-4550-5200-5

1.2. Recommended use and restrictions on use

Recommended use

Automotive. Adhesive Remover

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Flammable Aerosol: Category 1	2.1.2A Flammable Aerosol
Acute Toxicity (inhalation): Category 5	6.1E Acute toxicity (inhalation)
Serious Eye Damage/Irritation: Category 2	6.4A Irritating to the eye
Skin Corrosion/Irritation: Category 2	6.3A Irritating to the skin

Aspiration Hazard: Category 1	6.1E Aspiration Hazard
Carcinogenicity: Category 2	6.7B Suspected human carcinogen
Specific Target Organ Toxicity (single exposure): Category 1	6.9A Toxic to human target organs/systems
Specific Target Organ Toxicity (repeated exposure): Category 1	6.9A Toxic to human target organs/systems
Specific Target Organ Toxicity (single exposure): Category 3	6.9B Narcotic effects
Chronic Aquatic Toxicity: Category 2	9.1B Aquatic toxicity (chronic)
Acute Aquatic Toxicity: Category 2	9.1D Aquatic toxicity (acute)
No GHS Equivalent	9.3C Terrestrial vertebrate toxicity

2.2. Label elements

SIGNAL WORD

DANGER!

Symbols:

Flame | Exclamation mark | Health Hazard | Environment |

Pictograms



HAZARD STATEMENTS:

H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H229	Pressurized container: may burst if heated.
H333	May be harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H351	Suspected of causing cancer.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs: sensory organs
H372	Causes damage to organs through prolonged or repeated exposure: nervous system
H373	May cause damage to organs through prolonged or repeated exposure: sensory organs
H411	Toxic to aquatic life with long lasting effects.
H433	Harmful to terrestrial vertebrates.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251A	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280A	Wear eye/face protection.
P280E	Wear protective gloves.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P264B	Wash exposed skin thoroughly after handling.

Response:

P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P331	Do NOT induce vomiting.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see Notes to Physician on this label).
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50oC.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P403	Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Acetone	67-64-1	15 - 40
Solvent Naphtha (Petroleum), Light Aliphatic	64742-89-8	15 - 40
Xylene	1330-20-7	15 - 40
Ethylbenzene	100-41-4	1 - 12
Carbon Dioxide	124-38-9	3 - 7
Toluene	108-88-3	< 0.02

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

5.4. Hazchem code: 2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Acetone		ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcinogen
Acetone		New Zealand WES	TWA(8 hours):1185 mg/m3(500 ppm);STEL(15 minutes):2375 mg/m3(1000 ppm)	
Carbon Dioxide		ACGIH	TWA:5000 ppm;STEL:30000 ppm	
Carbon Dioxide		New Zealand WES	TWA(8 hours): 9000 mg/m3 (5000 ppm); STEL(15 minutes): 54000 mg/m3 (30000 ppm)	
Ethylbenzene		ACGIH	TWA:20 ppm	A3: Confirmed animal carcinogen.
Ethylbenzene		New Zealand WES	TWA(8 hours):434 mg/m3(100 ppm);STEL(15 minutes):543 mg/m3(125 ppm)	

Toluene	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen, Ototoxicant
Toluene	New Zealand WES	TWA(8 hours): 188 mg/m ³ (50 ppm)	Skin
Xylene	ACGIH	TWA:100 ppm;STEL:150 ppm	A4: Not class. as human carcinogen
Xylene	New Zealand WES	TWA(8 hours):217 mg/m ³ (50 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Fluoroelastomer

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Colour	Colourless
Odour	Solvent
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	-18.3 °C [@ 98,324.975 Pa] [<i>Test Method:</i> Closed Cup] [<i>Details:</i> Value for Liquid Content]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	0.81 g/ml
Relative density	0.81 [<i>Ref Std:</i> WATER=1]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	539 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	66.6 % weight [<i>Test Method:</i> calculated per CARB title 2]
Percent volatile	100 % weight
VOC less H2O & exempt solvents	823 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1]

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Chemical (aspiration) pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Solvent Naphtha (Petroleum), Light Aliphatic	Dermal	Rabbit	LD50 3,000 mg/kg
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic	Ingestion	Rat	LD50 > 5,000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Carbon Dioxide	Inhalation-Gas (4 hours)	Rat	LC50 > 53,000 ppm
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Acetone	Mouse	Minimal irritation
Xylene	Rabbit	Mild irritant
Solvent Naphtha (Petroleum), Light Aliphatic	Rabbit	Irritant
Ethylbenzene	Rabbit	Mild irritant
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Acetone	Rabbit	Severe irritant
Xylene	Rabbit	Mild irritant
Solvent Naphtha (Petroleum), Light Aliphatic	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Moderate irritant
Toluene	Rabbit	Moderate irritant

Sensitisation:

Skin Sensitisation

Name	Species	Value
Ethylbenzene	Human	Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Solvent Naphtha (Petroleum), Light Aliphatic	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Acetone	Not specified.	Multiple animal species	Not carcinogenic
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Solvent Naphtha (Petroleum), Light Aliphatic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation
Carbon Dioxide	Inhalation	Not classified for male reproduction	Mouse	LOAEL 350,000 ppm	not available
Carbon Dioxide	Inhalation	Not classified for development	Rat	LOAEL	24 hours

				60,000 ppm	
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Solvent Naphtha (Petroleum), Light Aliphatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

				nt		
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple	NOAEL Not	

				animal species	available	
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
Carbon Dioxide	Inhalation	heart bone, teeth, nails, and/or hair liver nervous system kidney and/or bladder respiratory system	Not classified	Rat	LOAEL 60,000 ppm	166 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks

Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Xylene	Aspiration hazard
Solvent Naphtha (Petroleum), Light Aliphatic	Aspiration hazard
Ethylbenzene	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Ecotoxic to the aquatic environment.**

Acute Aquatic Toxicity: Category 2 (HSNO 9.1D Aquatic toxicity)

Chronic Aquatic Toxicity: Category 2 (HSNO 9.1B Aquatic toxicity)

Ecotoxic to terrestrial vertebrates**9.3C Terrestrial vertebrate toxicity**

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Acetone		Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone		Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone		Crustacea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone		Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone		Water flea	Experimental	21 days	NOEC	1,000 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic		Fathead minnow	Estimated	96 hours	LL50	4.1 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic		Water flea	Estimated	48 hours	EL50	4.5 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic		Green algae	Experimental	72 hours	EL50	11 mg/l

Solvent Naphtha (Petroleum), Light Aliphatic		Water flea	Estimated	21 days	NOEL	2.6 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic		Green algae	Experimental	72 hours	NOEL	0.1 mg/l
Xylene		Activated sludge	Estimated	3 hours	NOEC	157 mg/l
Xylene		Green Algae	Estimated	72 hours	EC50	4.36 mg/l
Xylene		Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Xylene		Water flea	Estimated	48 hours	EC50	3.82 mg/l
Xylene		Green Algae	Estimated	72 hours	NOEC	0.44 mg/l
Xylene		Water flea	Estimated	7 days	NOEC	0.96 mg/l
Xylene		Rainbow trout	Experimental	56 days	NOEC	>1.3 mg/l
Ethylbenzene		Activated sludge	Experimental	49 hours	EC50	130 mg/l
Ethylbenzene		Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
Ethylbenzene		Green Algae	Experimental	96 hours	EC50	3.6 mg/l
Ethylbenzene		Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
Ethylbenzene		Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
Ethylbenzene		Water flea	Experimental	48 hours	EC50	1.8 mg/l
Ethylbenzene		Water flea	Experimental	7 days	NOEC	0.96 mg/l
Carbon Dioxide		Fish	Experimental	96 hours	LC50	112.2 mg/l
Carbon Dioxide		Atlantic Salmon	Experimental	43 days	NOEC	26 mg/l
Toluene		Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene		Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene		Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene		Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene		Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene		Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene		Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene		Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene		Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene		Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene		Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene		Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene		Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
----------	------------	-----------	----------	------------	-------------	----------

Acetone		Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	Non-standard method
Acetone		Experimental Biodegradation	28 days	BOD	78 % weight	OECD 301D - Closed bottle test
Solvent Naphtha (Petroleum), Light Aliphatic		Estimated Biodegradation	28 days	BOD	77.05 % BOD/ThBOD	OECD 301F - Manometric respirometry
Xylene		Experimental Photolysis		Photolytic half-life (in air)	1.4 days (t 1/2)	
Xylene		Experimental Biodegradation	28 days	BOD	90-98 % BOD/ThBOD	OECD 301F - Manometric respirometry
Ethylbenzene		Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	Non-standard method
Ethylbenzene		Experimental Biodegradation	28 days	CO2 evolution	70-80 %CO2 evolution/THC O2 evolution	ISO 14593 Inorg C Headspace
Carbon Dioxide		Data not available - insufficient			N/A	
Toluene		Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Toluene		Experimental Biodegradation	20 days	BOD	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Acetone		Experimental Bioconcentration		Log Kow	-0.24	Non-standard method
Solvent Naphtha (Petroleum), Light Aliphatic		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Xylene		Experimental BCF - Rainbow Trout	56 days	Bioaccumulation factor	25.9	
Ethylbenzene		Experimental BCF - Salmon	42 days	Bioaccumulation factor	1	Non-standard method
Carbon Dioxide		Experimental Bioconcentration		Log Kow	0.83	Non-standard method
Toluene		Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene		Experimental Bioconcentration		Log Kow	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

Material	CAS Number	Ozone Depletion Potential	Cure activator
acetone		0	

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Disposal of the aerosol dispenser (that may or may not contain any residual substance), may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN1950

Proper Shipping Name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Special Instructions: Limited quantity may apply

Hazchem Code: 2YE

IERG: 49

International Air Transport Association (IATA) - Air Transport

UN No.: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN1950

Proper Shipping Name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

HSNO Approval number HSR002517

Group standard name Aerosols (Flammable, Toxic [6.7]) Group Standard 2017

HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	3,000 L (aggregate water capacity)
Hazardous atmosphere zone	3,000 L (aggregate water capacity)
Fire extinguishers	One required for 3,000 L (aggregate water capacity)
Emergency response plan	3,000 L (aggregate water capacity)
Secondary containment	Not required
Tracking	Not required
Warning signage	3,000 L (aggregate water capacity)

SECTION 16: Other information**Revision information:**

Initial issue.

Document group:	28-2728-5	Version number:	1.00
Issue Date:	10/03/2021	Supersedes date:	Initial issue.

Key to abbreviations and acronyms**GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>