

Intended use

Mipa 2K-HS-Klarlack CC 14 Tix is a thixotropic, VOC-compliant High-Solid acrylic clearcoat for partial or complete coating of passenger cars and commercial vehicles and provides particularly high vertical stability and resistance to boiling when applied in thick layers. Mipa 2K-HS-Klarlack CC 14 Tix offers a brilliant finish and optimum flow on solvent-based or water-based basecoats. Thanks to its special formulation, Mipa 2K-HS-Klarlack CC 14 Tix generally guarantees improved process reliability compared to standard HS clearcoats.

On the one hand, there is very high vertical stability even at high processing temperatures. This effectively minimises the risk of coating defects due to runners when applied in thick layers.


On the other hand, Mipa 2K-HS-Klarlack CC 14 Tix is highly resistant to boiling. Therefore, coating horizontal surfaces such as roofs, front hoods, etc. is possible without any problems even when applied in very thick layers. This advantage also takes effect at high processing temperatures, as an increased tendency to boiling and sagging is to be expected here.

Mipa 2K-HS-Klarlack CC 14 Tix can be optimally polished immediately after forced drying and is highly resistant to all climatic conditions as well as to chemical agents and mechanical stress. Ready for use after mixing with the hardener.

Spreading rate: 10,0 - 12,0 m²/l

Processing instructions**Colour**

colourless

**Mixing ratio****Hardener**

Mipa 2K-HS-Härter

by weight (lacquer : hardener)

—

by volume (lacquer : hardener)

2 : 1

**Hardener****for complete paintwork**

Mipa 2K-HS-Härter HS 25

Mipa 2K-HS-Härter HS 35

for partial paintwork

Mipa 2K-HS-Härter HS 10

—

**Pot life**

50 min with Mipa 2K-HS-Härter HS 10 at 20 °C

70 - 90 min with Mipa 2K-HS-Härter HS 25 at 20 °C


70 - 90 min with Mipa 2K-HS-Härter HS 35 at 20 °C

**Thinner**

Mipa 2K-Verdünnung kurz V 10

Mipa 2K-Verdünnung V 25

Mipa 2K-Verdünnung lang V 40

**Spray viscosity****gravity spray gun**

20 - 24 s 4 mm DIN


Airmix/Airless

—



Application mode

Application mode	Hardener	pressure (bar)	nozzle (mm)	spray passes	Thinner
gravity spray gun (high pressure)	–	2 - 2,5	1,2 - 1,3	1,5	0 - 5
HVLP (low pressure)	–	2 - 2,2	1,2 - 1,3	1,5	0 - 5
HVLP / internal nozzle pressure	–	0,7	–	–	–



Flash-off time

1 - 3 min between coats
10 - 15 min prior to oven drying

Dry coat thickness

50 - 60 µm



Drying time

object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable
20 °C	15 - 25 min	6 - 7 h	24 h	–	–
60 °C	–	30 min	2 h	–	–
Infrared drying shortwave	–	8 min	–	–	–
Infrared drying mediumwave	–	10 - 15 min	–	–	–

Note

Storage:	for at least 3 years in unopened original container
VOC Regulation :	EU limit value for this product (category B/d): 420 g/l This product contains max. 420 g/l of VOC
Processing conditions:	From +10 °C and up to 80 % relative air humidity. Ensure an adequate air ventilation.
Processing instructions:	Optimum application: Apply a light continuous spray coat followed by 1 full spray coat.