

## Technical data sheet

05/2015

86A-18  
CEOLMIT

## UV-absorber additive

## Areas of use

Polyurethane sealers and top coats, nitrocellulose top coats.

## Technical data

<b>Solvents</b>	Aromatic hydrocarbons, Esters	
<b>Density</b>	1,000 ( $\pm 0,03$ )	kg/l
<b>Flashpoint</b>	< 21°C	Method: closed cup
<b>Solid content (weight)</b>	63 $\pm$ 1	% by weight

## Properties

Non-yellowing power: good

## Special instructions

Suggested quantity: limited degradation supports and woods

0,5% - 1%

High degradations supports

5%

This additive attenuate yellowing of light woods but does not avoid the yellowing of the film of the paint

## FOR INDUSTRIAL USE ONLY

N.B.: Data provided on this technical data sheet correspond to our best knowledge and experience. we assure consistency on the chemical-physical characteristics of our products, within the tolerance limits specified in our technical data sheets. Responsibility of final result of product application is fully up to the users, who shall make sure that the product corresponds to their own needs with regard to application system, to substrates used as well as to working conditions.

Technical Service tel. +39 051 770770 - fax +39 051 770521 - servizioclienti@sherwin.com

## Sherwin-Williams Italy S.r.l. - con unico socio

Sede legale ed Amministrativa: Via del Fiffò, 12 - 40065 Pianoro (BO) - Italia - C.P. 18 - tel. +39 051 770 511 - fax +39 051 777 737 - www.oece.it

Cod. Fisc. E Reg. Impr. Bo 08866930152 - P. IVA: IT 00494251200 - Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Società soggetta a direzione e coordinamento di: The Sherwin-Williams Company, USA