



TECHNICAL DATA SHEET No 712

U900 CAVITY WAX

GENERAL TECHNICAL DESCRIPTION

Anti-corrosive wax oil treatment.

Formulated to protect closed cavities of the car body (door frames, hood, fenders etc.)

Remains oily with exceptional resistance to humidity and road salts.

SURFACE

All closed parts (doors, bonnet and running boards) External underbody parts of the vehicle

PRETREATMENT/CLEANING OF SUBSTRATE



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER.

Make sure the surface is first wiped dry and then air dried.

PRODUCT APPLICATION



Shake well before using: 2 - 3 min



Pressure: 3 - 4 bar (44 - 58 psi) Apply via gun nozzle or

Apply via gun nozzle or extension tube provided, for hard-to-reach areas.

SPECIFIC GRAVITY

0.80 g/cm³

SOLID CONTENT (NO THINNER) 34% Weight

VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 840 g/L. 2004/42/IIB(e)(840)840

THEORETICAL COVERAGE

4 - 5 m^2 / l at 100 micron (4 mil) dry film thickness

CLEANING OF EQUIPMENT

Clean after final use with 767 NITRO THINNER



TS aun

• Allow for additional time for combi spray booths to reach the desired temperature

Best results when used with HB BODY




ucts



Protect from humidity and freeze



Always close tin after use



Guaranteed shelf life of 24 months in unused

original containers stored in a cool place

Always wear protective

STORAGE SHELF LIFE

(+5°C - +25°C) (41°F - 77°F).

equipment

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

NOVEMBER 2023