

TECHNICAL SHEET

TSP 190 – Finixa Etch Primer

Description

Finixa Etch primer is a fast drying, very smooth finishing and excellent corrosion protective primer. Direct over paintable with all A-brands water- or solvent based base coats.

Product features

- Excellent corrosive protection
- Fast drying
- Smooth finishing
- Direct over paintable
- Can be used on difficult substrate like aluminum and galvanized steel.
- Please consult SDS for more detailed info

Application

Surface preparation:

Make sure the surface is properly cleaned and degreased.

Process:

Always use in a well ventilated area with the proper personal protection (gloves, spray mask, glasses)

Step 1: Thoroughly shake the aerosol for 2 minutes

Step 2: Spray a full coat at a distance of +-25cm from the to be treated surface (+- 15µm, +-0.59mils)

Step 3: Flash-off 3'-5' before adding a second coat if necessary.

Step 4: leave to dry for 20' (curing times are influenced by temperate, humidity or layer thickness)

Optional, if needed, sand with:

- Dry sanding: P400 – P600
- Wet sanding: P600 – P800

Step 5: Overpaint with base coat.

Shelf life : 2 year after production.

Storage: keep in a dry well ventilated area and away from direct sunlight and frost, recommended temperature between 5°C - 41°F and 25°C - 77°C

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the product suitability for their own applications.