

in accordance with HSNO

Revision: 25.09.2023 Printing date 28.09.2023 Version number 36

1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: Mipatherm-Spray

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Paint

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MIPA SE

Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20

Fax.: +49 8703 92 21 00

e-mail: sdb-registratur@mipa-paints.com

www.mipa-paints.com

Importer in New Zealand:

RJP Performance Coatings 33 Ha Crescent, Wiri Auckland 2104 Phone: 09 25000 91 Email: sales@mipa.nz Web: www.mipa.nz

24HR Emergency Assistance in New Zealand:

National Poison Control Centre: 0800 POISON [764 766]

· Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

2 Hazards identification

· Classification of the substance or mixture



flame

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



STOT SE 3 H336

May cause drowsiness or dizziness.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

n-Butyl acetate **Xylene** propan-2-ol

Ethylbenzene

Hazard statements H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

123-86-4	n-Butyl acetate	25-50%
	🊸 Flam. Liq. 3, H226; 🕚 STOT SE 3, H336	1
74-98-6	propane	10-25%
	🚸 Flam. Gas 1A, H220; 🥎 Press. Gas L, H280	
75-28-5	isobutane	10-25%
	🚸 Flam. Gas 1A, H220; 🥎 Press. Gas C, H280	
106-97-8	butane, pure	10-25%
	🚸 Flam. Gas 1A, H220; 🥎 Press. Gas C, H280	
1330-20-7	Xylene	2.5-<5%
	♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
7429-90-5	aluminium powder (stabilized)/ manufacturer classification	<2.5%
	♦ Flam. Sol. 1, H228	
67-63-0	propan-2-ol	<2.5%
	🚸 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319; STOT SE 3, H336	
100-41-4	Ethylbenzene	<2.5%
	Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ♦ Asp. Tox. 1, H304; Flam. Liq. 4, H227	<2.5%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 2)

· Information for doctor:

Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Keep container tightly sealed.

· Storage class: 2 B

(Contd. on page 4)



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

Ingredients with lim	it values that require monitoring at the workplace:				
123-86-4 n-Butyl acetate					
WES (New Zealand)	Short-term value: 950 mg/m³, 200 ppm				
	Long-term value: 713 mg/m³, 150 ppm				
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm				
	Long-term value: 241 mg/m³, 50 ppm				
74-98-6 propane					
WES (New Zealand)	Simple asphyxiant; may present an explosion hazard				
106-97-8 butane, pu	re				
WES (New Zealand)	Long-term value: 1900 mg/m³, 800 ppm				
1330-20-7 Xylene					
WES (New Zealand)	Long-term value: 217 mg/m³, 50 ppm				
	oto				
IOELV (EU)	Short-term value: 442 mg/m³, 100 ppm				
	Long-term value: 221 mg/m³, 50 ppm				
	Skin				
	n powder (stabilized)/ manufacturer classification				
WES (New Zealand)	Long-term value: 10* 5** 2*** mg/m³				
	*metal dust;**welding fume,soluble salts;***alkyls				
67-63-0 propan-2-ol					
WES (New Zealand)	Short-term value: 1230 mg/m³, 500 ppm				
	Long-term value: 983 mg/m³, 400 ppm				
100-41-4 Ethylbenzene					
WES (New Zealand)	Short-term value: 176 mg/m³, 40 ppm				
	Long-term value: 88 mg/m³, 20 ppm				
	skin, oto				
IOELV (EU)	Short-term value: 884 mg/m³, 200 ppm				
	Long-term value: 442 mg/m³, 100 ppm				

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Skin

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

Change in condition

• Melting point/freezing point: Undetermined. • Initial boiling point and boiling range: -44.5 °C

Flash point:
 Flammability (solid, gas):
 Auto-ignition temperature:
 Auto-ignition temperature:

• Decomposition temperature: Not determined.

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.2 Vol %
 Upper: 10.9 Vol %
 Vapour pressure at 20 °C: 8,300 hPa
 Vapour pressure at 50 °C: 55 hPa

Density at 20 °C: 0.745 g/cm³ (DIN 53217)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

· water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 6)



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 5)

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

· VOC (EC) 84.26 % · Solids content (weight-%): 15.7 %

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

ΝZ



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:

Negetimenation Dioposar mass	be made according to official regulations.
Transport information	
UN-Number NZS, IMDG, IATA	UN1950
UN proper shipping name	
· NZS	UN1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
Transport hazard class(es)	
NZS	
2	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
2	
Class	2.1 Gases.
· Label	2.1
Packing group	
· NZS, IMDG, IATA	Void
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Gases.
Hazard identification number (Ke	
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum cap
	of 1 litre: Category A. For AEROSOLS w
	capacity above 1 litre: Category B. For W.
0	AEROSOLS: Category C, Clear of living quan
Segregation Code	SG69 For AEROSOLS with a maximum cap

of 1 litre:

(Contd. on page 8)

Segregation as for class 9. Stow "separated from"

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of

class 1 except for division 1.4.



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

	(Contd. of page 7
	class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· NZS · Limited quantities (LQ) · Transport category · Tunnel restriction code	1L 2 D
· IMDG · Limited quantities (LQ)	1L
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· HSNO Approval numbers				
123-86-4	n-Butyl acetate	HSR001091		
74-98-6	propane	HSR001010		
75-28-5	isobutane	HSR001003		
106-97-8	butane, pure	HSR000989		
1330-20-7	Xylene	HSR000983		
67-63-0	propan-2-ol	HSR001180		
100-41-4	Ethylbenzene	HSR001151		

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

NEW ZEALAND:

HSR002515 Aerosols (Flammable) Group Standard 2020

- · Signal word Danger
- · Hazard-determining components of labelling:

n-Butyl acetate

Xylene

propan-2-ol

Ethylbenzene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 9)



in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 8)

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H228 Flammable solid.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Contact:

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas Press. Gas L: Gases under pressure – Liquefied gas

(Contd. on page 10)





Safety Data Sheet in accordance with HSNO

Printing date 28.09.2023 Version number 36 Revision: 25.09.2023

Trade name: Mipatherm-Spray

(Contd. of page 9)

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Flam. Sol. 1: Flammable solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.