

1 Identification of the substance or mixture and of the supplier

- **Product identifier**
- **Trade name:** *Mipa Converter-Prefilled-Spray*
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Prefilled spray*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MIPA SE
Am Oberen Moos 1
D-84051 Essenbach
Tel.: +49(0)8703-922-0
Fax.: +49(0)8703-922-100
e-mail: sdb-registratur@mipa-paints.com
www.mipa-paints.com
- **Importer in New Zealand:**
RJP Performance Coatings
33 Ha Crescent, Wiri
Auckland 2104
Phone: 09 25000 91
Email: sales@mipa.nz
Web: www.mipa.nz
- **24HR Emergency Assistance in New Zealand:**
National Poison Control Centre: 0800 POISON [764 766]
- **Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

2 Hazards identification

- **Classification of the substance or mixture**



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

Hydrocarbons, C9, aromatics

Xylene

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 1)

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/Information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| 115-10-6 | dimethyl ether ⚠ Flam. Gas 1A, H220; ⚠ Press. Gas L, H280 | 25-50% |
| 67-64-1 | acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 25-50% |
| 64742-95-6 | Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336; Acute Tox. 5, H303; Acute Tox. 5, H313 | ≥2.5-<15% |
| 1330-20-7 | Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | 2.5-<5% |
| 71-36-3 | Butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | ≥2.5-<3% |

Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Seek immediate medical advice.

(Contd. on page 3)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire fighting measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B

(Contd. on page 4)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

| | |
|-------------------|-------------------------------------------------------------------------------------------------------|
| WES (New Zealand) | Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm |
| IOELV (EU) | Long-term value: 1920 mg/m ³ , 1000 ppm |

67-64-1 acetone

| | |
|-------------------|-----------------------------------------------------------------------------------------------------------------|
| WES (New Zealand) | Short-term value: 2375 mg/m ³ , 1000 ppm Long-term value: 1185 mg/m ³ , 500 ppm bio |
| IOELV (EU) | Long-term value: 1210 mg/m ³ , 500 ppm |

1330-20-7 Xylene

| | |
|-------------------|--------------------------------------------------------------------------------------------------------------|
| WES (New Zealand) | Long-term value: 217 mg/m ³ , 50 ppm oto |
| IOELV (EU) | Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin |

71-36-3 Butan-1-ol

| | |
|-------------------|-------------------------------------------------------|
| WES (New Zealand) | Ceiling limit: 150 mg/m ³ , 50 ppm skin |
|-------------------|-------------------------------------------------------|

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 4)

· **Breakthrough time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

· **Appearance:**

· **Form:**

Aerosol

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/freezing point:**

Undetermined.

· **Initial boiling point and boiling range:**

-24.9 °C

· **Flash point:**

<0 °C (DIN EN ISO 1523:2002)

· **Flammability (solid, gas):**

Not applicable.

· **Auto-ignition temperature:**

235 °C (DIN 51794)

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

· **Lower:**

0.7 Vol %

· **Upper:**

18.6 Vol %

· **Vapour pressure at 20 °C:**

5,200 hPa

· **Density at 20 °C:**

0.795 g/cm³ (DIN EN ISO 2811-1)

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not applicable.

· **Solubility in / Miscibility with**

· **water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:**

· **Dynamic:**

Not determined.

· **Kinematic:**

Not determined.

· **Solvent content:**

· **VOC (EC)**

87.10 %

· **Solids content (weight-%):**

12.9 %

· **Other information**

No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 6)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 5)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) : hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.



NZ

(Contd. on page 7)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 6)

14 Transport information

| | |
|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| · UN-Number | UN1950 |
| · NZS, IMDG, IATA | |
| · UN proper shipping name | UN1950 AEROSOLS |
| · NZS | AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |
| · Transport hazard class(es) | |
| · NZS | |
|  | |
| · Class | 2 5F Gases. |
| · Label | 2.1 |
| · IMDG, IATA | |
|  | |
| · Class | 2.1 Gases. |
| · Label | 2.1 |
| · Packing group | |
| · NZS, IMDG, IATA | Void |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Gases. |
| · Hazard identification number (Kemler code): - | |
| · EMS Number: | F-D,S-U |
| · Stowage Code | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · Segregation Code | |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · NZS | |
| · Limited quantities (LQ) | 1L |
| · Transport category | 2 |

(Contd. on page 8)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 7)

| | |
|----------------------------------|-----------------------|
| · Tunnel restriction code | D |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· HSNO Approval numbers

| | | |
|-----------|----------------|-----------|
| 115-10-6 | dimethyl ether | HSR000995 |
| 67-64-1 | acetone | HSR001070 |
| 1330-20-7 | Xylene | HSR000983 |
| 71-36-3 | Butan-1-ol | HSR001096 |

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

NEW ZEALAND:

| | |
|--------------|---------------------------------------|
| Class 2.1.2A | Flammable Aerosol |
| Class 6.1E | Aspiration Hazard |
| Class 6.4A | Eye Irritant |
| Class 6.9B | Target Organ – Repeat/Narcotic Effect |
| Class 9.1C | Aqua Toxic |

· Signal word Danger

HSR002515 Aerosols (Flammable)

· Hazard-determining components of labelling:

Hydrocarbons, C9, aromatics

Xylene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P3a** FLAMMABLE AEROSOLS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

(Contd. on page 9)

Trade name: Mipa Converter-Prefilled-Spray

(Contd. of page 8)

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

| Class | Share in % |
|-------|------------|
| NK | 50-100 |

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Contact:**

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas L: Gases under pressure – Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3