

## 1 Identification of the substance or mixture and of the supplier

- **Product identifier**
- **Trade name:** *Mipa BC-Verdünnung*
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** *Thinner, Diluent*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MIPA SE  
Am Oberen Moos 1  
D-84051 Essenbach  
Tel.: +49 8703 92 20  
Fax.: +49 8703 92 21 00  
e-mail: [sdb-registratur@mipa-paints.com](mailto:sdb-registratur@mipa-paints.com)  
[www.mipa-paints.com](http://www.mipa-paints.com)
- **Importer in New Zealand:**  
RJP Performance Coatings  
33 Ha Crescent, Wiri  
Auckland 2104  
Phone: 09 25000 91  
Email: [sales@mipa.nz](mailto:sales@mipa.nz)  
Web: [www.mipa.nz](http://www.mipa.nz)
- **24HR Emergency Assistance in New Zealand:**  
National Poison Control Centre: 0800 POISON [764 766]
- **Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

## 2 Hazards identification

- **Classification of the substance or mixture**



flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



health hazard

STOT RE 2      H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2      H315 Causes skin irritation.

Eye Irrit. 2      H319 Causes serious eye irritation.

STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS02   GHS07   GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labelling:**

*n*-Butyl acetate

Hydrocarbons, C9, aromatics

Xylene

**Trade name: Mipa BC-Verdünnung**

(Contd. of page 1)

**Ethylbenzene**

**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

**Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**3 Composition/Information on ingredients**

**Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

123-86-4	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	50-100%
64742-95-6	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	≥2.5-≤20%
1330-20-7	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319	5-≤10%
141-78-6	Ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H336	2.5-≤10%
100-41-4	Ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ Aquatic Chronic 3, H412	<2.5%

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures**

**General information:** Immediately remove any clothing soiled by the product.

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Immediately rinse with water.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Seek immediate medical advice.

(Contd. on page 3)

**Trade name: Mipa BC-Verdünnung**

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire fighting measures

- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3

(Contd. on page 4)

**Trade name: Mipa BC-Verdünnung**

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

### 123-86-4 n-Butyl acetate

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm

Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU)

Short-term value: 723 mg/m<sup>3</sup>, 150 ppm

Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

### 1330-20-7 Xylene

WES (New Zealand) Long-term value: 217 mg/m<sup>3</sup>, 50 ppm

oto

IOELV (EU)

Short-term value: 442 mg/m<sup>3</sup>, 100 ppm

Long-term value: 221 mg/m<sup>3</sup>, 50 ppm

Skin

### 141-78-6 Ethyl acetate

WES (New Zealand) Long-term value: 720 mg/m<sup>3</sup>, 200 ppm

IOELV (EU)

Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm

Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

### 100-41-4 Ethylbenzene

WES (New Zealand) Short-term value: 176 mg/m<sup>3</sup>, 40 ppm

Long-term value: 88 mg/m<sup>3</sup>, 20 ppm

skin, oto

IOELV (EU)

Short-term value: 884 mg/m<sup>3</sup>, 200 ppm

Long-term value: 442 mg/m<sup>3</sup>, 100 ppm

Skin

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

**Trade name: Mipa BC-Verdünnung**

(Contd. of page 4)



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

**General Information**

**Appearance:**

**Form:**

Fluid

**Colour:**

According to product specification

**Odour:**

Characteristic

**Odour threshold:**

Not determined.

**pH-value:**

Not determined.

**Change in condition**

**Melting point/freezing point:**

Undetermined.

**Initial boiling point and boiling range:**

77-78 °C

**Flash point:**

21 °C (DIN 53213)

**Flammability (solid, gas):**

Highly flammable.

**Auto-ignition temperature:**

370 °C (DIN 51794)

**Decomposition temperature:**

Not determined.

**Ignition temperature:**

Product is not selfigniting.

**Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

**Explosion limits:**

**Lower:**

0.7 Vol %

**Upper:**

7.5 Vol %

**Vapour pressure at 20 °C:**

97 hPa

**Vapour pressure at 50 °C:**

360 hPa

**Density at 20 °C:**

0.879 g/cm<sup>3</sup> (DIN 53217)

**Relative density**

Not determined.

**Vapour density**

Not determined.

**Evaporation rate**

Not determined.

**Solubility in / Miscibility with**

**water:**

Not miscible or difficult to mix.

**Partition coefficient: n-octanol/water:**

Not determined.

**Viscosity:**

**Dynamic:**

Not determined.

**Kinematic at 20 °C:**

10-15 s (DIN 53211/4)

**Solvent content:**

**VOC (EC)**

100.00 %

(Contd. on page 6)

**Trade name: Mipa BC-Verdünnung**

(Contd. of page 5)

- |                                     |  |
|-------------------------------------|--|
| · <b>Solids content (weight-%):</b> | 0.0 %                                      |
| · <b>Other information</b>          | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · **LD/LC50 values relevant for classification:**

#### 123-86-4 n-Butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) : hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)



**Trade name: Mipa BC-Verdünnung**



· **Other adverse effects** No further relevant information available.

(Contd. of page 6)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |   |                               |
|---|-------------------------------|
| · <b>UN-Number</b>  | UN1263                        |
| · <b>NZS, IMDG, IATA</b>  |                               |
| · <b>UN proper shipping name</b>  | UN1263 PAINT RELATED MATERIAL |
| · <b>NZS</b>  | PAINT RELATED MATERIAL        |
| · <b>IMDG, IATA</b>   |                               |
| · <b>Transport hazard class(es)</b>   |                               |
| · <b>NZS</b>  |                               |
|  |                               |
| · <b>Class</b>  | 3 (F1) Flammable liquids.     |
| · <b>Label</b>  | 3                             |
| · <b>IMDG, IATA</b>   |                               |
|  |                               |
| · <b>Class</b>  | 3 Flammable liquids.          |
| · <b>Label</b>  | 3                             |
| · <b>Packing group</b>  |                               |
| · <b>NZS, IMDG, IATA</b>  | II                            |
| · <b>Environmental hazards:</b>   |                               |
| · <b>Marine pollutant:</b>  | No                            |
| · <b>Special precautions for user</b>   | Warning: Flammable liquids.   |
| · <b>Hazard identification number (Kemler code):</b>                                | 33                            |
| · <b>EMS Number:</b>  | F-E, S-E                      |
| · <b>Stowage Category</b>   | B                             |
| · <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>         | Not applicable.               |
| · <b>Transport/Additional information:</b>  |                               |
| · <b>NZS</b>  |                               |
| · <b>Limited quantities (LQ)</b>  | 5L                            |
| · <b>Transport category</b>   | 2                             |

(Contd. on page 8)

**Trade name: Mipa BC-Verdünnung**

(Contd. of page 7)

· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>UN "Model Regulation":</b>	UN 1263 PAINT RELATED MATERIAL, 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **HSNO Approval numbers**

123-86-4	n-Butyl acetate	HSR001091
1330-20-7	Xylene	HSR000983
141-78-6	Ethyl acetate	HSR001041
100-41-4	Ethylbenzene	HSR001151

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

n-Butyl acetate

Hydrocarbons, C9, aromatics

Xylene

Ethylbenzene

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 9)



**Trade name: Mipa BC-Verdünnung**

(Contd. of page 8)

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	50-100

· **Other regulations, limitations and prohibitive regulations**

Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Approval Number: The HSNO Approval Number for this Group Standard is HSR002662.

Refer also to the Site & Storage requirements document.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· **Contact:**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**