CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1



1.0 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE SUPPLIER

Product Name:	Epoxy Resin
Product Code:	TP33
Recommended use:	Epoxy resin suitable for construction of fibre reinforced equipment and fittings. Suitable for construction of recreational water craft. Corrosion resistant flooring and coatings.
Supplier:	Adhesive Technologies NZ Limited
Street Address:	17 Corban Avenue, Henderson, Auckland
Telephone Number:	0064 9 838 6961 (8.00am to 5.00pm, Monday to Friday)
Facsimile:	0064 9 836 4849
Web Address	http://www.adhesivetechnologies.co.nz/
Emergency Telephone:	0064 3 479 7248 (From overseas)
National Poison Information Centre	0800 POISON (764 766) (within New Zealand)
New Zealand Fire Service	111
Date of issue	08/10/2024
Version	1.1

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

Hazard Classification

Acute Toxicity (Dermal):	Category 4
Acute Toxicity (Oral):	Category 4
Acute Toxicity (Inhalation):	Category 4
Skin Corrosion/Irritation:	Category 2
Serious Eye Damage/Eye Irritation:	Category 2A
Skin Sensitiser:	Category 1
Aquatic Toxicity (Chronic):	Category 2

For the full text of the H-Statements mentioned in this Section, see Section 16.



Signal Word: WARNING

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

CODE: TP33

Precautionary Statements

Hazards Statement

H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H411	Toxic to aquatic life with long-lasting effects

Prevention

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352	IF ON SKIN: wash with plenty of water.
P304+P340 P305+P351+P338 P330	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. Rinse mouth.
P332+P313	IF SKIN irritation occurs: Get medical advice/attention.
P333+P313	IF SKIN irritation or rash occurs: Get medical advice/attention.
P337+P313	IF eye irritation persists: Get medical advice/attention.

			SAFET		A SHI	EET
	CODE:	TP33	ISSUE DATE:	08/10/2024	REVISION:	1.1
P312 P363 P391		Call a POISON CENTER or docto Wash contaminated clothing be Collect spillage.	-	nwell.		
Storage P405		Store locked up				
Disposal P501		Dispose of contents/ container t Restricted to professional users		aste disposal	plant.	
Other ha	zards					

3.0 COMPOSITION / INFORMATION ON INGREDIENTS

Substance / Mixture: Mixture

Hazardous Ingredients:

Chemical Name	CAS No.	Concentration (%)
Bisphenol A/ epichlorohydrin resin	25085-99-8	50-70
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	9003-36-5	10-30
Benzyl alcohol	100-51-6	10-30
Other non-hazardous components		to 100

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in text.

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

4.0 FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre Phone 0800 764 766.

- Ingestion:Do not induce vomiting. Rinse mouth with water. Give plenty of water to drink.Inhalation:Remove victim to fresh air and provide oxygen if breathing is difficult. Give
artificial respiration if not breathing. Get medical attention.
- Skin Contact: Remove contaminated clothing/shoes and wipe excess from skin. Flush skin with water. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. Contaminated leather articles, including shoes, cannot be decontaminated, and should be destroyed to prevent reuse.
- Eye Contact:Flush eyes with plenty of water for 15 minutes while holding eyelids open. Get
medical attention.

Notes to physician: Treat symptomatically.

5.0 FIRE FIGHTING MEASURES

Hazards from combustion:	In case of fire, the following hazardous smoke fumes may be
	produced: Carbon Oxides, Nitrous gases, ammonia.
Suitable extinguishing media	Alcohol-resistant foam.
	Carbon dioxide (CO2).
	Dry chemical.
	Dry sand.
	Limestone powder.
Fire-fighting advice:	Clear fire area of all non-emergency personnel. Isolate fire and deny
	unnecessary entry. Cool fire exposed containers with water.

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in text.

Irritating fumes are released in fire situations. Move container from

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Do not allow material or run-off to enter waterways. Stay upwind, keep out of low areas. Wear positivepressure self-contained breathing apparatus (SCBA) and protective firefighting clothing (includes firefighting helmet, coat, trousers, boots, and gloves).

Avoid contact with this material during firefighting operations. If contact is likely, change to full chemical resistant firefighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location.

Suitable ExtinguishingUse water fog, foam, dry chemical, or carbon dioxide. Do not useMedia:direct water stream. May spread fireHazchem Code3Z

6.0 ACCIDENTAL RELEASE MEASURES

General Precautions:	Isolate area. Keep unnecessary and unprotected personnel from	
	entering the area. Use appropriate safety equipment. For additional	
	information, refer to Section 8, Exposure Controls and Personal	
	Protection. Refer to Section 7, Handling, for additional	
	precautionary measures.	
Personal Precautions:	Use cautious judgement when cleaning up spills. Shut off leaks, if	
	possible, without personal risk.	

CODE: TP33	ISSUE DATE: 08/10/2024 REVISION: 1.1
Environ-mental Precautions:	Dike and contain. Contain run-off and dispose of properly. Remove
	contaminated soil to remove contaminated trace residues. Prevent
	from entering drains, ditches, or rivers.
Clean-up Methods (small):	Soak up with an absorbent material such as clay, sand, sawdust or
	Zorball. Place in non-leaking container. Seal tightly for proper
	disposal.
For Large Spills:	Remove with vacuum trucks or pump to storage/salvage vessels.
	Soak up residue with an absorbent material such as clay, sand,
	sawdust or Zorball. Place in non-leaking container. Seal tightly for
	proper disposal. Flush is with water to remove trace residue.

7.0 HANDLING & STORAGE

Workplace Exposure Standards: Not established		
Engineering control	Use only with adequate ventilation. Use process enclosures, local exhaust	
measures:	ventilation or other engineering controls to keep worker exposure to	
	airborne contaminants as low as possible and/or below any	
	recommended or statutory limits. Use explosion-proof ventilation	
	equipment.	
Personal protective	Respiratory - Use a properly fitted, air-purifying or air-fed respirator	
equipment:	complying with an approved standard if a risk assessment indicates this is	
	necessary.	
	$\ensuremath{\textbf{Skin}}$ - Personal protective equipment for the body should be selected	
	based on the task being performed and the risks involved and should be	
	approved by a specialist before handling this product.	
	Eye - Safety eyewear complying with an approved standard should be used	
	when a risk assessment indicates this is necessary to avoid exposure to	
	liquid splashes, mists, gases, or dusts.	

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

Hand - Recommended: polyvinyl alcohol (PVA), Butyl rubber, EVAL,

Neoprene

8.0 EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredients with workplace control measures

Workplace Exposure Standards	None established
Engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants as low as possible and/or below any recommended or statutory limits. Use explosion-proof ventilation equipment.
Personal Protection	Respiratory - Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
	Skin - Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
	Eye - Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
	Hand - Recommended: polyvinyl alcohol (PVA), Butyl rubber, EVAL, Neoprene.

The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in text.

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

9.0 PHYSICAL & CHEMICAL PROPERTIES

Physical State	Liquid
Colour	Transparent / Colourless
Odour	Sweet odour
Melting/Freezing Point	Not available
Boiling Point	Not available
Flammability	Not available
Flammability Limits	Not available
Flash Point	251°C (closed cup)
Auto-ignition temperature	>300°C
рН	~5
Viscosity:	Not available
Vapour density	>1 (air =1)
Vapour pressure	82 Pa (4.5mm Hg)
Density:	1.5 – 1.7 g cm ⁻³ @ 25°C
Solubility (water)	Not Miscible

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

10.0 STABILITY & REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Conditions to avoid	Avoid temperatures above 300°C. Potentially violent decomposition can occur, causing gas generation and pressure increases in closed systems.
Materials to avoid	Heat is generated when mixed with water. Spattering and boiling can occur. Avoid contact with oxidizing materials. Avoid contact with: Acids. Acrylates. Alcohols. Aldehydes. Halogenated hydrocarbons. Ketones. Nitrites. Avoid contact with metals such as: Brass. Bronze. Copper. Copper alloys. Avoid contact with absorbent materials such as: Ground corn cobs. Moist organic absorbents. Peat moss. Sawdust.

11.0 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Information on toxicological effects

Potential Health effects

Vapours are unlikely due to physical properties. Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. Prolonged or repeated contact may cause skin irritation. May cause eye irritation. Corneal injury is unlikely.

Acute Health Effects

(Bisphenol A/ epichlorohydrin resin)

Test	Species	Result	Exposure
LD50 Oral	Rat	>5000mg/kg	-
LD50 Dermal	Rabbit	20,000mg/kg	-

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

Systemic	Except for Skin sensitization, repeated exposure is not likely to cause significant
Effects	adverse effects.
Carcinogenicity	IARC has classified DGEBPA as non-carcinogenic.
Mutagenicity	In animal studies, did not cause birth defects or other adverse effects on the foetus when pregnant rabbits, did not interfere with reproduction. Animal genetic toxicity studies were negative.

12.0 ECO-TOXICOLOGICAL INFORMATION

(Bisphenol A/ epichlorohydrin resin)

Ecotoxicity Material is moderately toxic to aquatic organisms on an acute basis

	Species	Period	Result
LC50	fathead minnow	96 h	3.1 mg/l
EC50	water flea	48 h	1.4 - 1.7 mg/
IC50	bacteria	18 h	> 42.6 mg/l

DegradabilityUnder OECD guidelines this material cannot be considered as readily degradable.BioaccumulationModerateLog Pow = 3 - 5

13.0 DISPOSAL CONSIDERATIONS

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal methods must follow all Federal, State/Provincial, and local laws and regulations.

FOR UNUSED AND UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: recycler, reclaimer, incinerator, or other destruction device.

General informationThe generation of waste should be minimised or avoided wherever possible. Thismaterial and its container must be disposed of in a safe way. Disposal of this

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible. Do not discharge into drains or watercourses or onto the ground.

14.0 TRANSPORTATION & REGULATORY INFORMATION

Road, Rail, Sea and Air Transport

UN Number	3082
Proper Shipping Nar	ne Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin Mixture)
DG Class	9
Packing Group	III
HAZCHEM code	3Z
IMO/IMDG class	9
ICAO/IATA class	9
EMS code	F–A, S–F
Marine pollutant	Yes

15.0 REGULATORY INFORMATION

EPA Approval:	The HSNO Approval Number for this Group Standard is HSR002670.
Group Standard:	Surface Coatings and Colourants (Corrosive) Group Standard 2020

CODE: TP33

ISSUE DATE: 08/10/2024 **REVISION:** 1.1

16.0 OTHER INFORMATION

References

https://echa.europa.eu/information-on-chemicals/cl-inventory-databas

https://www.epa.govt.nz/database-search/chemical-classification-and-information-database-ccid/

https://www.epa.govt.nz/

RCNZ Approved HSNO CoP Preparation of Safety Data Sheets

https://www.epa.govt.nz/assets/Uploads/Documents/Hazardous-Substances/GHS2/Guide_to_Classifying_Hazardous_Substances_in_NZ.pdf

While Adhesive Technologies NZ Limited believes that the information contained herein is based on data considered accurate, no warranty or representation is expressed or implied for which Adhesive Technologies NZ Limited assumes legal responsibility.

This version replaces all previous versions.

FOR FURTHER PRODUCT INFORMATION CALL ADHESIVE TECHNOLOGIES NZ LTD DURING BUSINESS HOURS

Product Information Manager (+64) 9 838 6961