



Safety Data Sheet

© 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	08-6601-2	Version number:	1.00
Issue Date:	01/07/2024	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

IDENTIFICATION:

1.1. Product identifier

3M™ Heavy-Bodied Seam Sealer, P.N. 08306, 08308

Product Identification Numbers

60-9800-3490-8

1.2. Recommended use and restrictions on use

Recommended use

Automotive. Two-part Epoxy Seam Sealer

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

08-6599-8, 08-6600-4

One or more components of this KIT is classified as a hazardous substance in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

TRANSPORT INFORMATION

Not Hazardous for Transport

Revision information:

Initial issue.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>



Safety Data Sheet

© 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	08-6599-8	Version number:	1.00
Issue Date:	01/07/2024	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08306, 08308

1.2. Recommended use and restrictions on use

Recommended use

Automotive., Seam Sealer Accelerator to be mixed at a 1:1 ratio with Sealer Base

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin sensitisation: Category 1

2.2. Label elements

SIGNAL WORD

Warning

Symbols:

Exclamation mark |

Pictograms



HAZARD STATEMENTS:

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

General

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280E Wear protective gloves.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	60 - 100
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	3 - 7
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	0.5 - 2
Triethylenetetramine	112-24-3	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Triethylenetetramine	112-24-3	AIHA	TWA:6 mg/m ³ (1 ppm)	Skin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Off-White
Odour	Mild Mercaptan
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	> 93.3 °C [Test Method:Closed Cup]
Evaporation rate	Not applicable.
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	Not applicable.
Vapor Density and/or Relative Vapor Density	Not applicable.
Density	1.18 g/cm ³
Relative density	1.18 [Ref Std:WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	1.7 % weight [Test Method:calculated per CARB title 2]
Volatile organic compounds (VOC)	20 g/l [Test Method:calculated SCAQMD rule 443.1]
Percent volatile	1.7 % weight
VOC less H ₂ O & exempt solvents	20 g/l [Test Method:calculated SCAQMD rule 443.1]

Particle Characteristics	Not applicable.
--------------------------	-----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.

10.6 Hazardous decomposition products

Substance	Condition
-----------	-----------

Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.
Oxides of nitrogen.	Not specified.
Oxides of sulphur.	Not specified.
Toxic vapour, gas, particulate.	Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Mercaptan-Terminated Epoxy Curing Agent	Dermal	Rabbit	LD50 > 10,200 mg/kg
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	Rat	LD50 2,600 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Propylene Oxide, Polymer With Triethylenetetramine	Dermal	Rat	LD50 2,150 mg/kg
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Rat	LD50 4,500 mg/kg

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08306, 08308

Triethylenetetramine	Dermal	Rabbit	LD50 550 mg/kg
Triethylenetetramine	Ingestion	Rat	LD50 2,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Mercaptan-Terminated Epoxy Curing Agent	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Propylene Oxide, Polymer With Triethylenetetramine	Rabbit	Irritant
Triethylenetetramine	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Mercaptan-Terminated Epoxy Curing Agent	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Propylene Oxide, Polymer With Triethylenetetramine	Rabbit	Severe irritant
Triethylenetetramine	Rabbit	Corrosive

Sensitisation:**Skin Sensitisation**

Name	Species	Value
Mercaptan-Terminated Epoxy Curing Agent	Mouse	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Propylene Oxide, Polymer With Triethylenetetramine	Mouse	Sensitising
Triethylenetetramine	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Mercaptan-Terminated Epoxy Curing Agent	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Propylene Oxide, Polymer With Triethylenetetramine	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350	during organogenesis

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08306, 08308

				mg/kg/day	
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	premating into lactation
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	43 days
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	premating into lactation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propylene Oxide, Polymer With Triethylenetetramine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	90 days
Mercaptan-Terminated Epoxy Curing Agent	Ingestion	endocrine system heart skin immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Propylene Oxide, Polymer With Triethylenetetramine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	43 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Ecotoxic to the aquatic environment.**

Acute Aquatic Toxicity: Category 3

Chronic Aquatic Toxicity: Category 3

No product test data available.

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08306, 08308

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Green algae	Experimental	72 hours	EC50	>733 mg/l
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Water flea	Experimental	48 hours	EC50	12 mg/l
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Zebra Fish	Experimental	96 hours	LC50	87 mg/l
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Green algae	Experimental	72 hours	NOEC	338 mg/l
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Water flea	Experimental	21 days	NOEC	3.5 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	Green algae	Experimental	72 hours	EC50	4.1 mg/l
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	Rainbow trout	Experimental	96 hours	LC50	>4.1 mg/l
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	Water flea	Experimental	48 hours	EC50	48 mg/l
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	Green algae	Experimental	72 hours	ErC10	0.11 mg/l
Propylene Oxide, Polymer With Triethylenetetramine	26950-63-0	Activated sludge	Experimental	3 hours	EC10	38 mg/l

mine						
Triethylenetetra mine	112-24-3	Green algae	Experimental	72 hours	EC50	27.4 mg/l
Triethylenetetra mine	112-24-3	Guppy	Experimental	96 hours	LC50	570 mg/l
Triethylenetetra mine	112-24-3	Water flea	Experimental	48 hours	EC50	37.4 mg/l
Triethylenetetra mine	112-24-3	Green algae	Experimental	72 hours	NOEC	0.468 mg/l
Triethylenetetra mine	112-24-3	Water flea	Experimental	21 days	NOEC	2.86 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Experimental Biodegradation	28 days	CO2 evolution	5 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Propylene Oxide, Polymer With Triethylenetetra mine	26950-63-0	Experimental Biodegradation	28 days	BOD	4 %BOD/ThO D	OECD 301F - Manometric respirometry
Propylene Oxide, Polymer With Triethylenetetra mine	26950-63-0	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
Triethylenetetra mine	112-24-3	Experimental Biodegradation	20 days	BOD	0 %BOD/ThO D	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Mercaptan-Terminated Epoxy Curing Agent	72244-98-5	Estimated Bioconcentrati on		Log Kow	>1.2	
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propylene Oxide, Polymer With Triethylenetetra mine	26950-63-0	Unknown Bioconcentrati on		Log Kow	-2.42	
Triethylenetetra	112-24-3	Experimental	42 days	Bioaccumulatio	<5.0	OECD305-

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08306, 08308

mine		BCF - Fish		n factor		Bioconcentration
------	--	------------	--	----------	--	------------------

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information**New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval number

HSR002670

Group standard name

Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020

3M™ Heavy-Bodied Seam Sealer - Accelerator, PN 08306, 08308

HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information

Revision information:

Initial issue.

Document group:	08-6599-8	Version number:	1.00
Issue Date:	01/07/2024	Supersedes date:	Initial issue.

Key to abbreviations and acronyms

GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the

user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>



Safety Data Sheet

© 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	08-6600-4	Version number:	1.00
Issue Date:	30/06/2024	Supersedes date:	Initial issue.

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08306, 08308

1.2. Recommended use and restrictions on use

Recommended use

Automotive. Two-part Epoxy Seam Sealer - Base

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Eye irritation: Category 2

Skin sensitisation: Category 1

Carcinogenicity: Category 2

Hazardous to the aquatic environment chronic: Category 2

2.2. Label elements

SIGNAL WORD

Warning

Symbols:

Exclamation mark |Health Hazard |

Pictograms



HAZARD STATEMENTS:

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280F	Wear respiratory protection.

Response

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	IF eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	70 - 80
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	20 - 30
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	1 - 10

Carbon black	1333-86-4	< 5
--------------	-----------	-----

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code:

Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of

the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m ³	A3: Confirmed animal carcinogen.
Carbon black	1333-86-4	New Zealand WES	TWA(8 hours): 3 mg/m ³	Suspected human carcinogen.

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08306, 08308

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Black
Odour	Mild Epoxy
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	> 115 °C [Test Method: Closed Cup]
Evaporation rate	Not applicable.
Flammability	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	Not applicable.
Vapor Density and/or Relative Vapor Density	Not applicable.
Density	1.16 g/cm ³
Relative density	1.16 [Ref Std: WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.

Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	6 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0.5 % weight [Test Method:calculated per CARB title 2]
Percent volatile	0.5 % weight
VOC less H2O & exempt solvents	6 g/l [Test Method:calculated SCAQMD rule 443.1]

Particle Characteristics	Not applicable.
--------------------------	-----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

Amines.

Strong acids.

10.6 Hazardous decomposition products

Substance	Condition
Aldehydes.	Not specified.
Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.
Toxic vapour, gas, particulate.	Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May cause additional health effects (see below).

Skin contact

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08306, 08308

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Rat	LD50 > 1,000 mg/kg
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Rat	LD50 > 2,000 mg/kg
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Mild irritant
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Minimal irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Moderate irritant
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Rabbit	Mild irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

Sensitisation:

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08306, 08308**Skin Sensitisation**

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Human and animal	Sensitising
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Mouse	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified

Respiratory Sensitisation

Name	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In vivo	Not mutagenic
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In vivo	Not mutagenic
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	during gestation

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08306, 08308

2,3-epoxypropane					
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	90 days
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	Ingestion	heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system vascular system skin muscles eyes respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	90 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 2

Chronic Aquatic Toxicity: Category 2

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Green algae	Estimated	72 hours	EC50	>11 mg/l
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Water flea	Estimated	48 hours	EC50	1.8 mg/l
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Green algae	Estimated	72 hours	NOEC	4.2 mg/l
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Water flea	Estimated	21 days	NOEC	0.3 mg/l

Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane						
4,4'-Isopropylidene dicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
4,4'-Isopropylidene dicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Green algae	Experimental	72 hours	EC50	>100 mg/l
4,4'-Isopropylidene dicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Rainbow trout	Experimental	96 hours	LC50	11.5 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-	25068-38-6	Estimated Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry

3M™ Heavy-Bodied Seam Sealer - Base (Part B) PN 08306, 08308

epoxypropane						
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Estimated Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
4,4'-Isopropylidene dicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Experimental Biodegradation	28 days	BOD	0.1 %BOD/Th OD	OECD 301D - Closed bottle test
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
4,4'-Isopropylidene diphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	25068-38-6	Estimated Bioconcentration		Log Kow	3.242	
4,4'-Isopropylidene dicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Experimental Bioconcentration		Log Kow	3.84	
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information**New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval number HSR002679

Group standard name Surface Coatings and Colourants (Carcinogenic) Group Standard 2020

HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for all other substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for all other substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information
Revision information:

Initial issue.

Document group:	08-6600-4	Version number:	1.00
Issue Date:	30/06/2024	Supersedes date:	Initial issue.

Key to abbreviations and acronyms

GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>