


## Valspar Refinish Direct to Mot

## Direct to Metal Primer

DTM2004 - Gray DTM2001 - White



It is designed using a combination of epoxy and acrylic polymers utilising isocyanate-free technology bundled to optimise performance in productivity, adhesion and durability.

## **Multi-Substrate Technology**

Valspar Refinish Direct to Metal Primer can be applied over all common automotive substrates, such as:

- Mild steel
- Aluminium
- Galvanised steel
- Fibreglass
- Sheet moulding composite (SMC)
- E-coat
- Existing OEM finishes

For more information on Valspar Refinish Direct to Metal Primer or any other product from the Valspar Refinish range visit **www.valsparrefinish.com.au** or contact your local Valspar Refinish Distributor.

\*Always refer to product TDS before use



Features	Benefits
A universal, multi-substrate primer with superior adhesion properties	No requirement for wash/ etch priming of bare panel areas, reducing application steps and paint consumption
Multi- substrate technology	Compatible with a variety of substrates reducing system complexity
4:1 mixing ratio	Easy mix ratio (accurate mixing with mixing stick or over the scales in ICRIS)
Excellent sprayability, flow and levelling	Excellent distinction of image and topcoat holdout
High Build (Primer Surfacer) and Wet-on-wet (Primer Sealer) application	Multi-functional properties providing flexibility for the user
Fast air dry characteristics (90 minutes at 20°C)	Prime and paint same day, increasing productivity
Excellent corrosion protection	High durable priming system offering long term protection
4:1 mixing ratio  Excellent sprayability, flow and levelling  High Build (Primer Surfacer) and Wet-on-wet (Primer Sealer) application  Fast air dry characteristics (90 minutes at 20°C)  Excellent corrosion	Easy mix ratio (accurate mixing with mixing stick or over the scales in ICRIS)  Excellent distinction of image and topcoat holdout  Multi-functional properties providing flexibility for the user  Prime and paint same day, increasing productivity  High durable priming system offering long term

Order Code	Product	Size
604006	DTM2001 Direct to Metal Primer - White	3.78 L
604008	DTM2004 Direct to Metal Primer - Gray	3.78 L
604011	DTMA Activator	0.946 L