

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:



1. Identification

Product Name: Brushable Seam Sealer

Product identifier: 100365

Relevant identified uses of the substance or mixture and uses advised against: Coating

Other means of identification

Chemical Manufacturer /
Importer / Distributor: ITW Evercoat
a division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, OH 45242
513-489-7600

Emergency telephone number: CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard

Symbols:



GHS Classification:

Reproductive Toxicity Category 1B
Hazardous to the aquatic environment - Acute Category 1
Hazardous to the aquatic environment - Chronic Category 1
Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Danger
GHS Hazard Statements: Highly flammable liquid and vapour.
Causes skin irritation.
May cause drowsiness or dizziness.
May damage fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.

GHS Signal Word:

GHS Hazard Statements:

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

GHS Precautionary Statements:

Safety Precautions:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.

First Aid Measures:

IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER or doctor/physician if you feel unwell.
Get medical advice/attention if you feel unwell.
Specific treatment (see on this label).
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use for extinction.
Collect spillage.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/container in accordance with
local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise classified:

Reports have associated repeated and prolonged occupational overexposure to
solvents with permanent brain and nervous system damage.

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Toluene	108-88-3	30 - 60
Butyl benzyl phthalate	85-68-7	10 - 30

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

trade secret.

4. First-aid measures

Eye Contact:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing before reuse.
Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down. If possible, do not leave individual unattended.
Most important symptoms/effects (Delayed:	Toluene may be harmful to the human fetus based on positive results with laboratory animals. Overexposure to Toluene has been suggested as a cause of the following effects in humans: cardiac sensitization, kidney damage. The substance may have effects on the central nervous system, resulting in decreased learning ability and psychological disorders. Butyl Benzyl Phthalate: This substance may have effects on the liver and kidneys, resulting in impaired functions.
Immediate medical attention and special treatment needed,:	No additional first aid information available

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

5. Fire-fighting measures

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical Water fog
Unsuitable extinguishing media:	No data available
Fire and/or Explosion Hazards:	Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.
Hazardous Combustion Products:	Toxic and corrosive gases,, Carbon dioxide, Carbon monoxide, Phthalic anhydride, Hydrocarbons
Special protective equipment and precautions for fire-fighters:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods and material for containment and cleaning up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

Conditions for safe storage: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry place For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with incompatible materials.

Materials to Avoid/Chemical Incompatibility:: Strong oxidizing agents

8. Exposure controls/personal protection

Limits:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Toluene	100 ppm	100 ppm	No data available

Appropriate engineering controls.: No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to protect against the splash of product.

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

Skin Protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres
Other Protective Equipment:	Splash proof chemical goggles are recommended to protect against the splash of product. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots
General Hygiene Conditions:	All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Do not take internally. Keep container closed when not in use. Keep out of the reach of children.

9. Physical and chemical properties

Appearance (physical state):	Liquid
Color:	Grey
Odor:	Aromatic
Odor threshold:	No data available
pH:	Neutral
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	111
Flash Point (°C):	4
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	7
Lower Flammable/Explosive Limit:	1
Vapor Pressure:	21 MMHG@20C/68F < 0.01 MMHG@20C/68F
Vapor Density:	Heavier than air. Vapors that evolve from this product

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

	will tend to settle and accumulate near the floor.
Relative Density:	1
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	No data available
Auto-ignition Temperature (°C):	480 °C
Decomposition Temperature::	No data available
Viscosity:	No data available
VOC (as packaged-less exempts and water)	3.42 or

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. .
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Toxic and corrosive gases, Carbon dioxide Carbon monoxide Phthalic anhydride Hydrocarbons

11. Toxicological information

Likely routes of exposure (inhalation, ingestion, skin and eye contact):	Ingestion, Skin contact, Eye contact, Absorption
--	--

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	Harmful if absorbed through the skin. May cause severe irritation and systemic damage. Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include redness, burning, drying and cracking of skin, and skin burns
Eye Contact:	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible. Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

Ingestion Toxicity: the lungs can cause chemical pneumonitis which can be fatal.
Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity: None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Reproductive and Developmental Toxicity: May damage fertility or the unborn child.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")

Skin Contact: Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Skin Absorption: Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available): Toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
Very toxic to aquatic life. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits. Butyl Benzyl Phthalate is very toxic to aquatic organisms. In the food chain this is important to humans, because bioaccumulation takes place, specifically in fish and seafood.

Persistence and degradability: No data available

Mobility in soil: No data available

Other adverse effects (such as hazardous to the ozone layer): No data available

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

Données sur l'écotoxicité

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues: Spent or discarded material is a hazardous waste.

Safe Handling of Waste: This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261).

Waste treatment methods (including packaging): Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste Disposal Code(s): D001

14. Transport information

UN number: UN1139

UN proper shipping name: COATING SOLUTION

Transport hazard class(es): 3

Packing group: II

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Statut TSCA: The intentional ingredients of this product are listed.

Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Toluene	108-88-3	N	N	Y	Y
Butyl benzyl phthalate	85-68-7	N	N	Y	Y

16. Other information, including date of preparation or last revision.

Revision Date: 12-14-2015

Revision Number: 6

Safety Data Sheet

Product Name: Brushable Seam Sealer

Product identifier: 100365

Revision Date: 12-14-2015

Replaces:

Disclaimer: **NOTICE:** The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances