

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	Weld-thru primer copper
Article number	TSP 530

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Industrial use Professional use
Uses advised against	Do not use for private purposes (household)

1.3 Details of the supplier of the safety data sheet

Chemicar Europe NV
Keetberglaan 1D
Haven 1087
9120 Melsele
Belgium

Telephone: +32 3 234 87 80
e-mail: msds@emm.com
Website: www.finixa.com

Additional information

Importer					
Country	Name	Street	City	Telephone	Website
New Zealand	Paint Smart Group NZ	10 Barberry Street	Judea, Tauranga	07 571 8921	www.paintsmart.co.nz

e-mail (competent person)	msds@emm.com
---------------------------	--------------

1.4 Emergency telephone number

Emergency information service	+31 38 4676600 This number is only available during the following office hours: Mon-Fri 09:00 - 17:00, CET: Central European Time
-------------------------------	--

Poison centre		
Country	Name	Telephone
New Zealand	National Poisons Centre	0800 764 766

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Hazard class	Category	Hazard class and category	Hazard statement
aerosols	1	Aerosol 1	H222,H229
skin corrosion/irritation	2	Skin Irrit. 2	H315
serious eye damage/eye irritation	1	Eye Dam. 1	H318
specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Hazard class	Category	Hazard class and category	Hazard statement
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of H-phrases: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

- signal word

Danger

- pictograms

GHS02, GHS05,
GHS07, GHS09



- hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

- precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- hazardous ingredients for labelling

Contains: butan-1-ol; Hydrocarbons, C9, aromatics; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; xylene.

2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

3.2 Mixtures

The product does not contain (other) ingredients which are classified according to present knowledge of the supplier and contribute to the classification of the product and hence require reporting in this section.

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
dimethyl ether	CAS No 115-10-6 EC No 204-065-8 REACH Reg. No 01-2119472128-37-xxxx	50 – < 75	Flam. Gas 1A / H220 Press. Gas C / H280	 	GHS-HC IOELV U(b)
Hydrocarbons, C9, aromatics	CAS No 128601-23-0 EC No 918-668-5 REACH Reg. No 01-2119455851-35-xxxx	10 – < 12.5	Flam. Liq. 3 / H226 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411 EUH066	   	
butan-1-ol	CAS No 71-36-3 EC No 200-751-6 REACH Reg. No 01-2119484630-38-xxxx	5 – < 10	Flam. Liq. 3 / H226 Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 STOT SE 3 / H335 STOT SE 3 / H336	  	GHS-HC
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC No 921-024-6 REACH Reg. No 01-2119475514-35-xxxx	5 – < 10	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411	   	
xylene	CAS No 1330-20-7 EC No 215-535-7 REACH Reg. No 01-2119488216-32-xxxx	2.5 – < 5	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT SE 3 / H336 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	  	C GHS-HC IOELV
copper [specific surface area > 0,67 mm2/mg]	CAS No 7440-50-8 EC No 231-159-6 REACH Reg. No 01-2119480154-42-xxxx	2.5 – < 5	Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		GHS-HC
ethylbenzene	CAS No 100-41-4 EC No 202-849-4 REACH Reg. No 01-2119489370-35-xxxx	< 2.5	Flam. Liq. 2 / H225 Acute Tox. 4 / H332 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	  	GHS-HC IOELV

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
reaction mass of ethylbenzene and xylene	EC No 905-588-0 REACH Reg. No 01-2119488216-32-xxxx	<2.5	Flam. Liq. 3 / H226 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 3 / H412	  	C

Notes

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

U(b): The allocation to the group 'compressed gas' is based on the physical state in which the gas is packaged

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
butan-1-ol	CAS No 71-36-3	-	-	500 mg/kg	oral
xylene	CAS No 1330-20-7	-	-	1,100 mg/kg 11 mg/l/4h	dermal inhalation: vapour
copper [specific surface area > 0,67 mm ² /mg]	CAS No 7440-50-8	-	M-factor (acute) = 10 M-factor (chronic) = 1	-	
reaction mass of ethylbenzene and xylene		-	-	1,100 mg/kg 11 mg/l/4h	dermal inhalation: vapour
ethylbenzene	CAS No 100-41-4	-	-	17.6 mg/l/4h	inhalation: vapour

Remarks

All the percentages given are percentages by weight unless stated otherwise. For full text of H-phrases: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. In case of unconsciousness place person in the recovery position. Never give anything by mouth. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice.

Following inhalation

Provide fresh air. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician.

Following skin contact

Wash with plenty of soap and water. Call a POISON CENTER/doctor.

Following eye contact

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Call a POISON CENTER or doctor if you feel unwell.

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects. Causes tears. Serious physical decay of vision. Causes burns. Redness.

4.3 Indication of any immediate medical attention and special treatment needed

For specialist advice physicians should contact the poison centre.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray; Dry extinguishing powder;
Co-ordinate firefighting measures to the fire surroundings.

Unsuitable extinguishing media

Water jet.

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

Hazardous combustion products

During fire hazardous fumes/smoke could be produced. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Self-contained breathing apparatus (SCBA). Standard protective clothing for firefighters.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Follow emergency procedures such as the need to evacuate the danger area or to consult an expert. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Remove persons to safety. Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases. Use personal protective equipment as required.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

°F.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- flammability hazards

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Protect from sunlight.

- incompatible substances or mixtures

Keep away from alkalis, oxidising substances, acids.

Control of effects

Protect against external exposure, such as

High temperatures. UV-radiation/sunlight.

Consideration of other advice

Store in a well-ventilated place. Keep container tightly closed.

- packaging compatibilities

Keep only in original container.

7.3 Specific end use(s)

See section 1.2.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

No information available.

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C9, aromatics	128601-23-0	DNEL	151 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	128601-23-0	DNEL	12.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C9, aromatics	128601-23-0	DNEL	32 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
Hydrocarbons, C9, aromatics	128601-23-0	DNEL	7.5 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
Hydrocarbons, C9, aromatics	128601-23-0	DNEL	7.5 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	2,035 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Relevant DNELs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	608 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	699 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		DNEL	699 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
butan-1-ol	71-36-3	DNEL	310 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
butan-1-ol	71-36-3	DNEL	55.36 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
butan-1-ol	71-36-3	DNEL	155 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
butan-1-ol	71-36-3	DNEL	3.125 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
butan-1-ol	71-36-3	DNEL	1.562 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
xylene	1330-20-7	DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
xylene	1330-20-7	DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
xylene	1330-20-7	DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
xylene	1330-20-7	DNEL	65.3 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
xylene	1330-20-7	DNEL	260 mg/m ³	human, inhalatory	consumer (private households)	acute - systemic effects
xylene	1330-20-7	DNEL	65.3 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
xylene	1330-20-7	DNEL	260 mg/m ³	human, inhalatory	consumer (private households)	acute - local effects
xylene	1330-20-7	DNEL	125 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
xylene	1330-20-7	DNEL	2.5 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	1 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Relevant DNELs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	137 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	273 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	1 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	1 mg/m ³	human, inhalatory	consumer (private households)	acute - local effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	137 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	273 mg/kg bw/day	human, dermal	consumer (private households)	acute - systemic effects
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	DNEL	0.041 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
reaction mass of ethylbenzene and xylene		DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
reaction mass of ethylbenzene and xylene		DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	65.3 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	260 mg/m ³	human, inhalatory	consumer (private households)	acute - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	65.3 mg/m ³	human, inhalatory	consumer (private households)	chronic - local effects
reaction mass of ethylbenzene and xylene		DNEL	260 mg/m ³	human, inhalatory	consumer (private households)	acute - local effects
reaction mass of ethylbenzene and xylene		DNEL	125 mg/kg bw/day	human, dermal	consumer (private households)	chronic - systemic effects
reaction mass of ethylbenzene and xylene		DNEL	2.5 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Relevant DNELs of components of the mixture						
Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
lene						
ethylbenzene	100-41-4	DNEL	77 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
ethylbenzene	100-41-4	DNEL	293 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
ethylbenzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
ethylbenzene	100-41-4	DNEL	15 mg/m ³	human, inhalatory	consumer (private households)	chronic - systemic effects
ethylbenzene	100-41-4	DNEL	1.6 mg/kg bw/day	human, oral	consumer (private households)	chronic - systemic effects

Relevant PNECs of components						
Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
dimethyl ether	115-10-6	PNEC	0.155 mg/l	aquatic organisms	freshwater	short-term (single instance)
dimethyl ether	115-10-6	PNEC	0.016 mg/l	aquatic organisms	marine water	short-term (single instance)
dimethyl ether	115-10-6	PNEC	160 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
dimethyl ether	115-10-6	PNEC	0.681 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
dimethyl ether	115-10-6	PNEC	0.069 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
dimethyl ether	115-10-6	PNEC	0.045 mg/kg	terrestrial organisms	soil	short-term (single instance)
butan-1-ol	71-36-3	PNEC	0.082 mg/l	aquatic organisms	freshwater	short-term (single instance)
butan-1-ol	71-36-3	PNEC	0.008 mg/l	aquatic organisms	marine water	short-term (single instance)
butan-1-ol	71-36-3	PNEC	2,476 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
butan-1-ol	71-36-3	PNEC	0.324 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
butan-1-ol	71-36-3	PNEC	0.032 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
butan-1-ol	71-36-3	PNEC	0.017 mg/kg	terrestrial organisms	soil	short-term (single instance)
xylene	1330-20-7	PNEC	0.327 mg/l	aquatic organisms	water	intermittent release
xylene	1330-20-7	PNEC	0.044 mg/l	aquatic organisms	freshwater	short-term (single instance)
xylene	1330-20-7	PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)
xylene	1330-20-7	PNEC	1.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
xylene	1330-20-7	PNEC	2.52 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Relevant PNECs of components						
Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
						instance)
xylene	1330-20-7	PNEC	0.252 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
xylene	1330-20-7	PNEC	0.852 mg/kg	terrestrial organisms	soil	short-term (single instance)
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	PNEC	6.3 µg/l	aquatic organisms	freshwater	short-term (single instance)
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	PNEC	5.2 µg/l	aquatic organisms	marine water	short-term (single instance)
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	PNEC	230 µg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	PNEC	87 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	PNEC	676 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	PNEC	65 mg/kg	terrestrial organisms	soil	short-term (single instance)
reaction mass of ethylbenzene and xylene		PNEC	0.044 mg/l	aquatic organisms	freshwater	short-term (single instance)
reaction mass of ethylbenzene and xylene		PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)
reaction mass of ethylbenzene and xylene		PNEC	1.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
reaction mass of ethylbenzene and xylene		PNEC	2.52 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
reaction mass of ethylbenzene and xylene		PNEC	0.252 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
reaction mass of ethylbenzene and xylene		PNEC	0.852 mg/kg	terrestrial organisms	soil	short-term (single instance)
ethylbenzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	water	intermittent release
ethylbenzene	100-41-4	PNEC	0.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
ethylbenzene	100-41-4	PNEC	0.01 mg/l	aquatic organisms	marine water	short-term (single instance)
ethylbenzene	100-41-4	PNEC	9.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ethylbenzene	100-41-4	PNEC	13.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
ethylbenzene	100-41-4	PNEC	1.37 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Relevant PNECs of components						
Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
ethylbenzene	100-41-4	PNEC	2.68 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation. Provide eyewash stations and safety showers at the workplace.

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection

Skin protection



Chemical protective clothing.

Hand protection



Wear suitable gloves. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- type of material

Butyl rubber

- material thickness

Use gloves with a minimum material thickness: $\geq 0,40$ mm.

- breakthrough time of the glove material

Use gloves with a minimum breakthrough time of the glove material: >480 minutes (permeation: level 6).

- other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment. In case of inadequate ventilation wear respiratory protection. Type: ABEK-P2 (combined filters against gases, vapours and particles, colour code: Brown/Grey/Yellow/Green/White).

Environmental exposure controls

Take appropriate precautions to avoid uncontrolled release into the environment. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, solid, gaseous (spray aerosol)
Colour	copper
Odour	like solvents
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	-24.8 °C calculated value, referring to a component of the mixture

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	LEL: 0.7 vol% / UEL: 26.2 vol%
Flash point	not applicable
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases)) calculated value, referring to a component of the mixture
Decomposition temperature	no data available
pH (value)	not determined
Kinematic viscosity	not relevant
Solubility	not determined

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	4,000 hPa at 20 °C
-----------------	--------------------

Density and/or relative density

Density	0.8 g/cm³ at 20 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers.

10.6 Hazardous decomposition products

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
butan-1-ol	71-36-3	oral	500 mg/kg
xylene	1330-20-7	dermal	1,100 mg/kg
xylene	1330-20-7	inhalation: vapour	11 mg/l/4h
reaction mass of ethylbenzene and xylene		dermal	1,100 mg/kg
reaction mass of ethylbenzene and xylene		inhalation: vapour	11 mg/l/4h
ethylbenzene	100-41-4	inhalation: vapour	17.6 mg/l/4h

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
dimethyl ether	115-10-6	inhalation: gas	LC50	164,000 ppmV/4h	rat
Hydrocarbons, C9, aromatics	128601-23-0	oral	LD50	7,093 mg/kg	rat
Hydrocarbons, C9, aromatics	128601-23-0	dermal	LD50	>2,000 mg/kg	rabbit
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		inhalation: vapour	LC50	>25.2 mg/l/4h	rat
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		dermal	LD50	>2,800 – 3,100 mg/kg	rat
butan-1-ol	71-36-3	oral	LD50	2,292 mg/kg	rat
butan-1-ol	71-36-3	dermal	LD50	3,430 mg/kg	rabbit
xylene	1330-20-7	oral	LD50	5,627 mg/kg	mouse
xylene	1330-20-7	dermal	LD50	12,126 mg/kg	rabbit
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	oral	LD50	>2,500 mg/kg	rat
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	dermal	LD50	>2,000 mg/kg	rat
reaction mass of ethylbenzene and xylene		inhalation: vapour	LC50	27,124 mg/m ³ /4h	rat
reaction mass of ethylbenzene and xylene		oral	LD50	6,631 mg/kg	rat
reaction mass of ethylbenzene and xylene		dermal	LD50	12,126 mg/kg	rabbit
ethylbenzene	100-41-4	inhalation: va-	LC50	17.6 mg/l/4h	rat

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
		pour			
ethylbenzene	100-41-4	oral	LD50	3,500 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

Other information

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
dimethyl ether	115-10-6	LC50	$>4.1 \text{ g/l}$	guppy (Poecilia reticulata)	96 h
dimethyl ether	115-10-6	EC50	$>4.4 \text{ g/l}$	daphnia magna	48 h
dimethyl ether	115-10-6	NOEC	$\geq 4.1 \text{ g/l}$	guppy (Poecilia reticulata)	96 h
Hydrocarbons, C9, aromatics	128601-23-0	LL50	9.2 mg/l	rainbow trout (Oncorhynchus mykiss)	96 h
Hydrocarbons, C9, aromatics	128601-23-0	EL50	3.2 mg/l	daphnia magna	48 h
Hydrocarbons, C9, aromatics	128601-23-	NOELR	1 mg/l	algae	72 h

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
	0				
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		LL50	>13.4 mg/l	rainbow trout (Onco-rhynchus mykiss)	96 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EL50	≥10 – ≤22 mg/l	daphnia magna	24 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		NOELR	6.3 mg/l	algae	72 h
butan-1-ol	71-36-3	ErC50	225 mg/l	algae	96 h
butan-1-ol	71-36-3	LC50	1,376 mg/l	fathead minnow (Pimephales promelas)	96 h
butan-1-ol	71-36-3	EC50	1,328 mg/l	daphnia magna	48 h
butan-1-ol	71-36-3	NOAEC	129 mg/l	algae	96 h
butan-1-ol	71-36-3	NOEC	519 mg/l	fathead minnow (Pimephales promelas)	96 h
xylene	1330-20-7	ErC50	4.7 mg/l	algae	72 h
xylene	1330-20-7	EL50	5.267 mg/l	algae	72 h
xylene	1330-20-7	LC50	5.549 mg/l	rainbow trout (Onco-rhynchus mykiss)	72 h
xylene	1330-20-7	LL50	5.921 mg/l	rainbow trout (Onco-rhynchus mykiss)	72 h
xylene	1330-20-7	EC50	5.744 mg/l	algae	72 h
xylene	1330-20-7	NOELR	1.009 mg/l	algae	72 h
xylene	1330-20-7	NOEC	1.1 mg/l	algae	72 h
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	LC50	1,100 µg/l	bluegill (Lepomis macrochirus)	96 h
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	EC50	792 µg/l	daphnia magna	48 h
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	NOEC	13 µg/l	fathead minnow (Pimephales promelas)	96 h
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	LOEC	0.006 mg/l	unknown	96 h
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	growth (EbCx) 10%	7.98 µg/l	aquatic invertebrates	48 h
reaction mass of ethylbenzene and xylene		ErC50	4.7 mg/l	algae	72 h
reaction mass of ethylbenzene and xylene		EL50	5.267 mg/l	algae	72 h
reaction mass of ethylbenzene and xylene		LC50	5.089 mg/l	rainbow trout (Onco-rhynchus mykiss)	72 h
reaction mass of ethylbenzene and xylene		LL50	5.921 mg/l	rainbow trout (Onco-rhynchus mykiss)	72 h
reaction mass of ethylbenzene and xylene		EC50	5.267 mg/l	algae	72 h
reaction mass of ethylbenzene and xylene		NOELR	1.009 mg/l	algae	72 h
reaction mass of ethylbenzene and		NOEC	1.009 mg/l	algae	72 h

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
xylene					
ethylbenzene	100-41-4	LC50	5.1 mg/l	fish	96 h
ethylbenzene	100-41-4	EC50	1.8 – 2.4 mg/l	daphnia magna	48 h
ethylbenzene	100-41-4	NOEC	3.3 mg/l	fish	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C9, aromatics	128601-23-0	EC50	>99 mg/l	microorganisms	10 min
Hydrocarbons, C9, aromatics	128601-23-0	NOEC	>99 mg/l	microorganisms	10 min
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EL50	1.6 mg/l	daphnia magna	21 d
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		EC50	0.23 mg/l	daphnia magna	21 d
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		NOELR	1 mg/l	daphnia magna	21 d
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		NOEC	0.17 mg/l	daphnia magna	21 d
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		LOEC	0.32 mg/l	daphnia magna	21 d
butan-1-ol	71-36-3	EC50	18 mg/l	daphnia magna	21 d
butan-1-ol	71-36-3	NOEC	4.1 mg/l	daphnia magna	21 d
butan-1-ol	71-36-3	growth (EbCx) 10%	2,476 mg/l	soil microorganisms	17 h
xylene	1330-20-7	ErC50	4.36 mg/l	algae	73 h
xylene	1330-20-7	EL50	2.9 mg/l	daphnia magna	21 d
xylene	1330-20-7	EC50	2.2 mg/l	algae	73 h
xylene	1330-20-7	NOEC	1.063 mg/l	rainbow trout (Onco-rhynchus mykiss)	21 d
xylene	1330-20-7	LOEC	1.29 mg/l	zebra fish (Danio rerio)	35 d
xylene	1330-20-7	NOELR	1.989 mg/l	daphnia magna	21 d
xylene	1330-20-7	growth (EbCx) 10%	1.91 mg/l	daphnia magna	21 d
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	EC50	0.032 mg/l	green algae	7 d
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	LC50	61.2 µg/l	unknown	28 d
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	NOEC	123 µg/l	fish	12 d
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	LOEC	0.22 mg/l	unknown	0.17 min
copper [specific surface area > 0,67 mm ² /mg]	7440-50-8	growth (EbCx)	1.02 µg/l	fish	25 d

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
0,67 mm2/mg]		10%			
reaction mass of ethylbenzene and xylene		ErC50	4.36 mg/l	algae	73 h
reaction mass of ethylbenzene and xylene		EL50	2.9 mg/l	daphnia magna	21 d
reaction mass of ethylbenzene and xylene		EC50	2.2 mg/l	algae	73 h
reaction mass of ethylbenzene and xylene		NOEC	0.975 mg/l	rainbow trout (Onco-rhynchus mykiss)	21 d
reaction mass of ethylbenzene and xylene		LOEC	1.29 mg/l	zebra fish (Danio rerio)	35 d
reaction mass of ethylbenzene and xylene		NOELR	1.989 mg/l	daphnia magna	21 d
reaction mass of ethylbenzene and xylene		growth (EbCx) 10%	1.91 mg/l	daphnia magna	21 d
ethylbenzene	100-41-4	EC50	2.8 mg/l	aquatic invertebrates	24 h
ethylbenzene	100-41-4	LC50	3.6 mg/l	crustacean	7 d
ethylbenzene	100-41-4	LOEL	1.7 mg/l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEC	1.7 mg/l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	NOEC	0.262 mg/l	fish	30 d

12.2 Persistence and degradability

Degradability of components					
Name of substance	CAS No	Process	Degradation rate	Time	Method
dimethyl ether	115-10-6	oxygen depletion	5 %	28 d	
Hydrocarbons, C9, aromatics	128601-23-0	oxygen depletion	30.9 %	2 d	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		oxygen depletion	10.5 %	15 d	
butan-1-ol	71-36-3	oxygen depletion	68 %	5 d	
xylene	1330-20-7	oxygen depletion	94 %	28 d	
reaction mass of ethylbenzene and xylene		oxygen depletion	94 %	28 d	

12.3 Bioaccumulative potential

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
dimethyl ether	115-10-6		0.07 (25 °C)	
Hydrocarbons, C9, aromatics	128601-23-0	≥30.85 – ≤467	3.03 – 4.73 (20 °C)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		≥26.26 – ≤315.7	2.96 – 3.78 (20 °C)	

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butan-1-ol	71-36-3		1 (25 °C)	
xylene	1330-20-7	56.49	3.12 (20 °C)	
reaction mass of ethylbenzene and xylene		>5.5 – <12.2	3.12 (20 °C)	
ethylbenzene	100-41-4	110	3.6 (20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste (Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids
H11 Toxic (Delayed or chronic)

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

UN RTDG	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

UN RTDG	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

UN RTDG	2.1
IMDG-Code	2.1

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

ICAO-TI	2.1
14.4 Packing group	not assigned
14.5 Environmental hazards	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	Hydrocarbons, C9, aromatics
14.6 Special precautions for user	
There is no additional information.	
14.7 Maritime transport in bulk according to IMO instruments	
No data available.	

Additional information for each of the UN Model Regulations

Transport information - national regulations - additional information (UN RTDG)

UN number	1950
Class	2.1
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959 (UN RTDG)
Excepted quantities (EQ)	E0 (UN RTDG)
Limited quantities (LQ)	1 L (UN RTDG)

International Maritime Dangerous Goods Code (IMDG) - additional information

Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	-

International Civil Aviation Organization (ICAO-IATA/DGR) - additional information

Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	2.1



Special provisions (SP)	A145, A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	30 kg

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

This Safety Data Sheet is purely informative and does comply with EU regulations, but not with country-specific regulations.

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Name	Name acc. to inventory	Restriction	No
xylene	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
xylene	flammable / pyrophoric	R40	40
xylene	substances in tattoo inks and permanent make-up	R75	75
ethylbenzene	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
ethylbenzene	flammable / pyrophoric	R40	40
Hydrocarbons, C9, aromatics	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
Hydrocarbons, C9, aromatics	flammable / pyrophoric	R40	40
butan-1-ol	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
butan-1-ol	flammable / pyrophoric	R40	40
butan-1-ol	substances in tattoo inks and permanent make-up	R75	75
dimethyl ether	flammable / pyrophoric	R40	40
reaction mass of ethylbenzene and xylene	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
reaction mass of ethylbenzene and xylene	flammable / pyrophoric	R40	40
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC	R3	3
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	flammable / pyrophoric	R40	40
copper [specific surface area > 0,67 mm ² /mg]	substances in tattoo inks and permanent make-up	R75	75

Legend

R3

- Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ash-trays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
- Articles not complying with paragraph 1 shall not be placed on the market.
- Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
- Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
- Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Legend

- lamps – may lead to life-threatening lung damage”;
- (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: ‘Just a sip of grill lighter fluid may lead to life threatening lung damage’;
- (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.’;
- R40**
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,
 - ‘whoopie’ cushions,
 - silly string aerosols,
 - imitation excrement,
 - horns for parties,
 - decorative flakes and foams,
 - artificial cobwebs,
 - stink bombs.
 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: ‘For professional users only’.
 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
- R75**
1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
 - (a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitizer category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:
 - (i) 0,1 % by weight, if the substance is used solely as a pH regulator;
 - (ii) 0,01 % by weight, in all other cases;
 - (e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:
 - (i) “Rinse-off products”;
 - (ii) “Not to be used in products applied on mucous membranes”;
 - (iii) “Not to be used in eye products”;
 - (g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;
 - (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.
 2. For the purposes of this entry use of a mixture “for tattooing purposes” means injection or introduction of the mixture into a person’s skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.
 3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.
 4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
 - (a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
 - (b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).
 5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.
 6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.
 7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:
 - (a) the statement “Mixture for use in tattoos or permanent make-up”;
 - (b) a reference number to uniquely identify the batch;
 - (c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Legend

the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;

(d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;

(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;

(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;

(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.

The information shall be clearly visible, easily legible and marked in a way that is indelible.

The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.

Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

None of the ingredients are listed.

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100 200	56)

Notation

56) hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

Directive on industrial emissions (VOCs, 2010/75/EU)

VOC content	82.6 %
-------------	--------

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name acc. to inventory	CAS No	Remarks	Threshold for releases to air (kg/year)
xylene, mixture of isomers	1330-20-7	(17) (11)	
ethylbenzene	100-41-4	(11)	
copper	7440-50-8	(8)	100

Legend

- (11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded
- (17) Total mass of xylene (ortho-xylene, meta-xylene, para-xylene)
- (8) All metals shall be reported as the total mass of the element in all chemical forms present in the release

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
xylene	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	
ethylbenzene	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	
copper [specific surface area > 0,67 mm ² /mg]	Metals and their compounds		a)	

Legend

a) Indicative list of the main pollutants

Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors, amending Regulation (EC) No 1907/2006 and repealing Regulation (EU) No 98/2013

None of the ingredients are listed.

Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

Restrictions of occupation

Directive 94/33/EC on the protection of young people at work / Observe national regulations on protection of young people at work.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding / Observe national regulations on maternity protection.

National regulations (New Zealand)

New Zealand Inventory of Chemicals (NZIoC)

All ingredients are listed or exempt from listing.

Group standard approval: HSR002515 - Aerosols (Flammable) Group Standard 2020.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Abbr.	Descriptions of used abbreviations
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
log KOW	n-Octanol/water
M-factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
NOAEC	No Observed Adverse Effect Concentration

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Abbr.	Descriptions of used abbreviations
NOEC	No Observed Effect Concentration
NOELR	No Observed Effect Loading Rate
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Press. Gas	Gas under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

Weld-thru primer copper

Version number: 1.0

Date of compilation: 2026-07-08

Code	Text
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.