SAFETY DATA SHEET



9-851 WaterBase Degreaser

Section 1. Identification

Product name : 9-851 WaterBase Degreaser

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in coatings - Cleaner.

Supplier

Manufacturer : Valspar b.v.

Zuiveringweg 89 8243 PE Lelystad The Netherlands

tel: +31 (0)320 292200 fax: +31 (0)320 292201

Emergency telephone

number

: Call: +31 (0)320 292200 (during daytime)

Supplier's details : DBNZ Coatings Limited

6 Killarney Lane Hamilton 3204 NEW ZEALAND T: +64 7847 0944 E: info@dbnz.co.nz

Emergency telephone number (with hours of

operation)

: New Zealand Poisons Information Centre: 0800 764766 (24 hrs)

CALL: +(64)-98010034 (Hours of operation - 24 hours)

e-mail address of person responsible for this SDS

: msds@de-beer.com

Section 2. Hazards identification

HSNO Classification: FLAMMABLE LIQUIDS - Category 3

EYE IRRITATION - Category 2

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements

Signal word : Warning

Hazard statements : Flammable liquid and vapour.

Causes serious eye irritation.

Precautionary statements

Prevention: Wear protective gloves, protective clothing, eye protection, face protection, or

hearing protection. Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Wash thoroughly after handling.

Response : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists:

Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

9-851 WaterBase Degreaser

Page: 2/10

Section 2. Hazards identification

Symbol

Ingestion





Other hazards which do not : None known. result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
Isopropyl alcohol	7.5	67-63-0
1-methoxy-2-propanol	7.4782	107-98-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation : Remo

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse.

Clean shoes thoroughly before reuse.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.

Eye contact : Causes serious eye irritation.

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.Skin: No specific data.

Section 4. First aid measures

Eyes

: Adverse symptoms may include the following:

pain or irritation watering redness

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments

: Not available.

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable

: Use dry chemical, CO2, water spray (fog) or foam.

Not suitable

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Hazchem code

: 3Y

Special precautions for firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits		
Isopropyl alcohol	NZ HSWA 2015 (New Zealand, 2/2013). WES-STEL: 1230 mg/m³ 15 minutes. WES-STEL: 500 ppm 15 minutes. WES-TWA: 983 mg/m³ 8 hours. WES-TWA: 400 ppm 8 hours.		
1-methoxy-2-propanol	NZ HSWA 2015 (New Zealand, 11/2018). WES-STEL: 553 mg/m³ 15 minutes. WES-STEL: 150 ppm 15 minutes. WES-TWA: 369 mg/m³ 8 hours. WES-TWA: 100 ppm 8 hours.		

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: EN 14387 organic vapour filter (Type A)

Section 8. Exposure controls/personal protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 butyl rubber neoprene >= 0.4 mm

< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (>= 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: chemical splash goggles.

Skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Colourless.

Odour : Not available.

Odour threshold : Not available.

pH : 7 to 8 [Conc. (% w/w): 100%]

Melting point: Not available.Boiling point: 100°C (212°F)

Flash point : Closed cup: 41°C (105.8°F)

Open cup: Not applicable. [Product does not sustain combustion.]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapour pressure : Not available.
Vapour density : 2.1 [Air = 1]
Relative density : 0.973

Solubility : Easily soluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not applicable.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Aerosol product

Type of aerosol : Not applicable.

Heat of combustion : Not available.

Ignition distance : Not applicable.

Enclosed space ignition - : Not applicable.

Time equivalent

Page: 6/10

Section 9. Physical and chemical properties

Enclosed space ignition -

Deflagration density

: Not applicable.

Flame height : Not applicable. Flame duration : Not applicable.

Section 10. Stability and reactivity

Chemical stability

The product is stable.

reactions

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials:

oxidising materials

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure

Inhalation : No known significant effects or critical hazards. Ingestion No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards.

Eve contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data. Ingestion : No specific data. **Skin contact** No specific data.

Eye contact : Adverse symptoms may include the following:

> pain or irritation watering redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl alcohol	LD50 Dermal LD50 Oral	Rabbit Rat	13900 mg/kg 5840 mg/kg	-
1-methoxy-2-propanol	LD50 Dermal LD50 Oral	Rabbit	2000 mg/kg 4016 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	_	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
1-methoxy-2-propanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Sensitisation

Version Date of issue/Date of revision: 6/4/2022 : 1

Section 11. Toxicological information

Not available

Potential chronic health effects

General : No known significant effects or critical hazards.Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact: No known significant effects or critical hazards.

Eye contact : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Chronic toxicity

Not available.

Carcinogenicity

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity

Not available.

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	26744.22 mg/kg

Section 12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
Isopropyl alcohol	Acute EC50 >100 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute LC50 9640 mg/l	Fish - Pimephales promelas	96 hours
1-methoxy-2-propanol	Acute EC50 >1000 mg/l	Aquatic plants - Selenastrum capricornutum	96 hours
	Acute EC50 >21000 mg/l Acute LC50 6812 mg/l	Daphnia - Daphnia magna Fish - Leuciscus idus	48 hours 96 hours

Persistence/degradability

Section 12. Ecological information

Product/ingredient name	Test	Result		Dose	Inoculum
1-methoxy-2-propanol	OECD 301E 301E Ready Biodegradability - Modified OECD Screening Test	96 % - 28 days		-	-
Product/ingredient name	Aquatic half-life		Photolysi	S	Biodegradability
Isopropyl alcohol	-		-		Readily Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
1 1 7	0.05		low
1-methoxy-2-propanol	<1	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
New Zealand Class	UN1263	PAINT RELATED MATERIAL	3	III	PLAMMASE PLAMMASE
ADG Class	UN1263	PAINT RELATED MATERIAL	3	III	
UN Class	UN1263	PAINT RELATED MATERIAL	3	III	
ADR/RID Class	UN1263	PAINT RELATED MATERIAL	3	III	

9-851 WaterBase Degreaser Page: 9/10

Section 14. Transport information

IATA Class	UN1263	Paint related material	3	III	
IMDG Class	UN1263	PAINT RELATED MATERIAL	3	III	

Additional information

New Zealand Class : <u>Hazchem code</u> 3Y

Special provisions 163, 223

ADG Class : <u>Hazchem code</u> •3Y

Special provisions 163, 223, 367

UN Class : <u>Special provisions</u> 163, 223, 367

ADR/RID Class : <u>Hazard identification number</u> 30

Limited quantity 5 L

Special provisions 163, 650, 367

Tunnel code (D/E)

IATA Class : Quantity limitation Passenger and Cargo Aircraft: 60 L. Packaging instructions:

355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities -

Passenger Aircraft: 10 L. Packaging instructions: Y344.

<u>Special provisions</u> A3, A72, A192

IMDG Class : **Emergency schedules** F-E, _S-E_

Special provisions 163, 223, 367, 955

PG* : Packing group

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

HSNO Approval Number : HSR002528 **HSNO Group Standard** : Cleaning Products

HSNO Classification : FLAMMABLE LIQUIDS - Category 3

EYE IRRITATION - Category 2

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

9-851 WaterBase Degreaser

Section 15. Regulatory information

Japan : Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined

New Zealand : All components are listed or exempted.
Philippines : All components are listed or exempted.
Republic of Korea : All components are listed or exempted.
Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : Not determined.

Viet Nam : Not determined.

Section 16. Other information

History

Date of printing : 6/4/2022 Date of issue/Date of : 6/4/2022

revision

Date of previous issue : 4/12/2022

Version : 1

Key to abbreviations : ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

Page: 10/10

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References : 2004/42/IIB(a)(200)199

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.