

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Finixa primer dark grey 400ml
UFI	: X5C7-SHGU-1P95-9HNP
Product code	: TSP 130
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Use of the substance/mixture	: Coating solution

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Importer

Paint Smart Group NZ
10 Barberry Street
Judea
Tauranga
New Zealand
www.paintsmart.co.nz

Supplier

Chemical Europe NV
Baarbeek, 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number	: Poisons Information Centre New Zealand 0800 764 766
------------------	----------------------------------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

HSR002517 – Flammable, toxic

Adverse physicochemical, human health and environmental effects

No additional information available

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: butanone; ethyl methyl ketone

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear eye protection/face protection.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTRE or doctor if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Nordic countries regulation

Denmark

MAL code

: 4-1

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

butanone; ethyl methyl ketone

Component

butanone; ethyl methyl ketone(78-93-3)	
----------------------------------------	--

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8	25 – 50	Flam. Gas 1A, H220 Press. Gas
butanone; ethyl methyl ketone	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
acetone; propan-2-one; propanone substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336
trizinc bis(orthophosphate)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6	2.5 – 10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : No irritant effect.
- First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Get medical advice/attention if you feel unwell.
- First-aid measures after ingestion : Do not induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam. Water fog. Carbon dioxide. extinguishing powder.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- Protection during firefighting : Approved respirator.

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Keep public away.

6.1.1. For non-emergency personnel

Emergency procedures : Keep public away.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow product to spread into the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Provide adequate ventilation.

Methods for cleaning up : Do not flush with water.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure adequate air ventilation. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Store in dry, cool, well-ventilated area. Protect from heat and direct sunlight. Keep containers closed.

Special rules on packaging : Container should not be closed gas-tight. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

dimethyl ether (115-10-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Dimethylether
IOEL TWA	1920 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Oxyde de diméthyle # Dimethylether
OEL TWA	1920 mg/m ³
OEL TWA [ppm]	1000 ppm

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dimethyl ether (115-10-6)	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
acetone; propan-2-one; propanone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Acétone # Aceton
OEL TWA	594 mg/m ³
OEL TWA [ppm]	246 ppm
OEL STEL	1187 mg/m ³
OEL STEL [ppm]	492 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Keep away from food, drink and animal feedingstuffs. Take off immediately all contaminated clothing. Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes. Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles (EN 166). Safety glasses (EN 166)

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin and body protection	
Type	Standard
	EN 13034

Hand protection:

Wear gloves according to EN374 resistant to the solvent(s) in use. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Nitrile rubber gloves	Nitrile rubber (NBR)	5 (> 240 minutes)	>0.5		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

Wear suitable respiratory equipment in case of insufficient ventilation

Respiratory protection			
Device	Filter type	Condition	Standard
	Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust		

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: dark grey.
Appearance	: Aerosol.
Molecular mass	: > g/mol
Odour	: characteristic.
Odour threshold	: > ppm
Melting point	: Not applicable
Freezing point	: Not applicable
Boiling point	: -24.8 °C
Flammability	: Not self-igniting
Explosive limits	: Not available
Lower explosion limit	: 1.5 vol %
Upper explosion limit	: 18.6 vol %
Flash point	: -42 °C
Auto-ignition temperature	: 235 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not applicable
Solubility	: Practically not miscible. Organic solvent:
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 5200 hPa
Vapour pressure at 50°C	: Not available

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Density	: 0.875 g/cm ³
Relative density	: Not applicable
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Dust deflagration index : < bar·m/s

9.2.2. Other safety characteristics

VOC content : 648.6 g/l VOC-CH 74.13%
Other properties : Flammable or explosive vapour/air mixtures may be formed,
Solid content :

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional data.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No dangerous reactions known under normal conditions of use.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

butanone; ethyl methyl ketone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

acetone; propan-2-one; propanone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Finixa primer dark grey 400ml

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

12.3. Bioaccumulative potential

Finixa primer dark grey 400ml

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

Finixa primer dark grey 400ml

Additional information	No supplementary information available
------------------------	----------------------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Refer to section 11.

12.7. Other adverse effects

Other adverse effects : Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment
---------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
	AEROSOLS MARINE POLLUTANT	Not applicable	
Transport document description			
UN 1950 , 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS MARINE POLLUTANT, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 , 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 , 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Transport regulations (ADR)	: Subject to the provisions
Classification code (ADR)	: 5F
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tunnel restriction code (ADR) : D

Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E0
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

No data available

Inland waterway transport

Classification code (ADN) : 5F

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3.	butanone; ethyl methyl ketone ; acetone; propan-2-one; propanone ; n-butyl acetate
3(a)	butanone; ethyl methyl ketone ; acetone; propan-2-one; propanone ; n-butyl acetate
3(b)	butanone; ethyl methyl ketone ; acetone; propan-2-one; propanone
40.	dimethyl ether ; butanone; ethyl methyl ketone ; acetone; propan-2-one; propanone ; n-butyl acetate

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 648.6 g/l VOC-CH 74.13%

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives_en

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Waterbevaarlijkheid : 6 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1
Store unit : 1 liter
Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
-----------------	-----------------------------------------------------------------

Finixa primer dark grey 400ml

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.