

Technical Information Sheet

Valspar bv Zuiveringweg 89 8243 PE Lelystad The Netherlands tel: +31 (0)320 292200 fax: +31 (0)320 292201

1-10 Washprimer Hardener

APPLICATION DATA



Mixing Ratio

: 1:1 (Washprimer:Hardener)



Application viscosity
DINCUP 4mm/20°C

: Airspray (sec) : Pressure tank (sec) : Airless (sec) : -

-





Nozzle diameter (mm)

Spraying pressure (bar)

HVLP / LVLP - See Info Manufacterer
HR - See Info Manufacterer



Spray coats / Layer thickness (µm)

: -/-



Flash-off (min)



Drying time (min) 20°C : -

60°C Obj. : -



Potlife (min) 20°C :

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.

Date of issue : 5/6/2008. Version : 3.1 / 1-10 / Page: 1/2



Technical Information Sheet

Valspar bv Zuiveringweg 89 8243 PE Lelystad The Netherlands tel: +31 (0)320 292200 fax: +31 (0)320 292201

1-10 Washprimer Hardener



Area of application : Hardener for 1-15.

Chemical base : Phosphoric acid in mild solvents.

General qualities : In combination with Washprimer 1-15, for use as primer with etching and

passivating properties.

Auxiliary materials : 1-15

Physical properties Specific gravity (kg/l) : 0.841

Flash point : Closed cup: 14°C (57.2°F)

Vol.% solids : 0 Economy : -Gloss :

Colour : Clear.

Substrates : See info 1-15

Undercoats : 1-15

Finishing materials : See info 1-15

Cleaning the equipment : 1-051 Gun Cleaner

Storage life (years) : min. 2

(Under normal storage conditions and unopened tins).

The technical data in these publications are based on our present knowledge and give you an idea of the various applications without obligations.

Date of issue : 5/6/2008. Version : 3.1 / 1-10 / Page: 2/2