



1-70 Epoxy Primer Hardener

APPLICATION DATA



Mixing Ratio

: 2:1 (Primer:Hardener), add 0-20% 1-141/1-151/1-161.



Application viscosity DINCUP 4mm/20°C

: Airspray (sec) : -
: Pressure tank (sec) : -
: Airless (sec) : -

-



Gravity feed
Suction feed
Pressure tank
Airless
HVLP / LVLP
HR

Nozzle diameter (mm)

-
-
-
-
-
-


Spraying pressure (bar)

-
-
-
-
See Info Manufacturer
See Info Manufacturer



Spray coats / Layer thickness (µm)

: - / -



Flash-off (min)

: -



Drying time (min)

20°C : -
60°C Obj. : -



Potlife (min)

20°C : -

1-70 Epoxy Primer Hardener



PRODUCT INFO

- Area of application** : Hardener for 1-75/1-7510.
- Chemical base** : Polyamino-amide combination
- General qualities** : Combined with Epoxy Primer 1-75 / 1-7510, a high-filling Epoxy Primer with excellent resistance to chemicals.
- Auxiliary materials** : 1-75/1-7510, 1-141/1-151/1-161

| | | |
|----------------------------|--------------------------------|------------------------------|
| Physical properties | Specific gravity (kg/l) | : 0.892 |
| | Flash point | : Closed cup: 4.5°C (40.1°F) |
| | Vol.% solids | : 27 |
| | Economy | : - |
| | Gloss | : |
| | Colour | : Yellowish. |

- Substrates** : See info 1-75/1-7510
- Undercoats** : See Info 1-75/1-7510
- Finishing materials** : See info 1-75/1-7510
- Cleaning the equipment** : 1-051 Gun Cleaner
- Storage life (years)** : min. 2
(Under normal storage conditions and unopened tins).