

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Wheel spray silver - light & ultrafine 400ml
UFI	: SMR9-DV9Y-4N97-E5PK
Product code	: TSP 520
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use, Consumer use
Use of the substance/mixture	: Non industrial spraying Industrial spraying

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Importer
Paint Smart Group NZ
10 Barberry Street
Judea
Tauranga
New Zealand
[www. Paintsmart.co.nz](http://www.Paintsmart.co.nz)

Supplier
Chemical Europe NV
Baarbeek, 2
2070 Zwijndrecht
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89
info@chemicar.eu

1.4. Emergency telephone number

Emergency number : Poisons Informations Centre New Zealand 0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Full text of H- and EUH-statements: see section 16	

HSR002515 – Aerosols (Flammable)

Adverse physicochemical, human health and environmental effects

No additional information available

Wheel spray silver - light & ultrafine 400ml


Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

EUH-statements

- : Danger
- : acetone; propan-2-one; propanone, n-butyl acetate, 2-methoxy-1-methylethyl acetate
- : H222 - Extremely flammable aerosol.
- : H229 - Pressurised container: May burst if heated.
- : H319 - Causes serious eye irritation.
- : H336 - May cause drowsiness or dizziness.
- : P103 - Read carefully and follow all instructions.
- : P102 - Keep out of reach of children.
- : P101 - If medical advice is needed, have product container or label at hand.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- : P211 - Do not spray on an open flame or other ignition source.
- : P251 - Do not pierce or burn, even after use.
- : P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- : P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- : P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- : EUH066 - Repeated exposure may cause skin dryness or cracking.
- : Without adequate ventilation formation of explosive mixtures may be possible.

Nordic countries regulation

Denmark

MAL code

: 4-3

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
dimethyl ether	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8	10 – 25	Flam. Gas 1A, H220 Press. Gas
propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5	10 – 25	Flam. Gas 1A, H220 Press. Gas

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0	2.5 – 10	Flam. Gas 1A, H220 Press. Gas
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7	2.5 – 10	Flam. Liq. 3, H226
isobutane (containing ≥ 0,1% butadiene (203-450-8))	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-01-8	2.5 – 10	Flam. Gas 1A, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340
Nitrocellulose, nitrogen content <12,6%	CAS-No.: 9004-70-0	2.5 – 10	Expl. 1.1, H201
ethanol; ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	< 2.5	Flam. Liq. 2, H225
xylene	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9	1 – 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
aluminium powder (stabilised)	CAS-No.: 7429-90-5 EC-No.: 231-072-3 EC Index-No.: 013-002-00-1	< 2.5	Water-react. 2, H261 Flam. Sol. 1, H228

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : After contact with skin, wash immediately with plenty of water and soap.
- First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Get medical advice/attention if you feel unwell.
- First-aid measures after ingestion : Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray jet. Dry powder. Carbon dioxide. Alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

No additional information available

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.3. Advice for firefighters

Protection during firefighting : Self-contained breathing apparatus. Do not breathe fumes from fires or vapours from decomposition.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Keep public away.

6.1.1. For non-emergency personnel

Emergency procedures : Keep public away.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow product to spread into the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Provide adequate ventilation.

Methods for cleaning up : SECTION 13.

6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure adequate air ventilation. Handle and open container with care. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Protect from heat and direct sunlight. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Store in dry, cool, well-ventilated area. Keep away from food, drink and animal feeding stuffs.

Special rules on packaging : Container should not be closed gas-tight. Store in a closed container.

7.3. Specific end use(s)

No additional information available

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

acetone; propan-2-one; propanone (67-64-1)	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm
dimethyl ether (115-10-6)	
WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm
butane, pure (106-97-8)	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)
n-Butyl acetate (123-86-4)	
WEL	Short-term value: 966 mg/m ³ , 200 ppm
	Long-term value: 724 mg/m ³ , 150 ppm
2-Methoxy-1-methylethyl acetate (108-65-6)	
WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
	Sk
Ethanol (64-17-5)	
WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
Xylene (1330-20-7)	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
aluminium powder (stabilized)/ manufacturer classification (7429-90-5)	
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-Butyl acetate (123-86-4)

Ingredients with biological limit values:

Xylene (1330-20-7)

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles (EN 166)

Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear gloves according to EN374 resistant to the solvent(s) in use. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Long term exposure		5 (> 240 minutes)			EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection

Device	Filter type	Condition	Standard
Self-contained breathing apparatus (SCBA)	Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Long term exposure	

8.2.2.4. Thermal hazards

No additional information available

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.3. Environmental exposure controls

Other information:

Keep away from food and drink. Take off immediately all contaminated clothing. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Avoid contact with skin and eyes.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: Product description.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: $\geq -44.5\text{ }^{\circ}\text{C}$
Flash point	: $< 0\text{ }^{\circ}\text{C}$
Auto-ignition temperature	: $235\text{ }^{\circ}\text{C}$
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 8300 hPa
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 0.743 g/cm^3 (20°C) (DIN53217)
Solubility	: Practically not miscible. Organic solvent:
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 1.7 vol %
Upper explosive limit (UEL)	: 18.6 vol %

9.2. Other information

VOC content	: 92.6 %
-------------	----------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

No decomposition when used according to regulations.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

acetone; propan-2-one; propanone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

Wheel spray silver - light & ultrafine 400ml

Persistence and degradability	No information available.
-------------------------------	---------------------------

12.3. Bioaccumulative potential

Wheel spray silver - light & ultrafine 400ml

Bioaccumulative potential	No information available.
---------------------------	---------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830





SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Do not dispose of with domestic waste. Do not discharge into drains.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 04 - metallic packaging 14 06 03* - other solvents and solvent mixtures

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
	Not applicable	Not applicable	
Transport document description			
UN 1950 , 2.1, (D)	UN 1950 , 2.1	UN 1950 , 2.1	UN 1950 , 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Transport regulations (ADR)	: Subject to the provisions
Classification code (ADR)	: 5F
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Tunnel restriction code (ADR)	: D

Transport by sea

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E0
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Air transport

No data available

Inland waterway transport

Classification code (ADN) : 5F

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3.	acetone; propan-2-one; propanone ; n-butyl acetate
3(a)	acetone; propan-2-one; propanone ; n-butyl acetate
3(b)	acetone; propan-2-one; propanone
40.	dimethyl ether ; acetone; propan-2-one; propanone ; n-butyl acetate

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 92.6 %

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Waterbezwaarlijkheid : 6 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken
SZW-lijst van kankerverwekkende stoffen : ethanol; ethyl alcohol is listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : ethanol; ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : ethanol; ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : ethanol; ethyl alcohol, xylene are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
	Without adequate ventilation formation of explosive mixtures may be possible
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Carc. 1A	Carcinogenicity, Category 1A
EUH066	Repeated exposure may cause skin dryness or cracking.
Expl. 1.1	Explosives, Division 1.1

Wheel spray silver - light & ultrafine 400ml

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
H201	Explosive; mass explosion hazard.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H261	In contact with water releases flammable gases.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.